NBS TECHNICAL NOTE 499

Multiple Scattering Corrections for the Associated-Particle Neutron Time-of-Flight Technique

U.S. DEPARTMENT OF COMMERCE
NATIONAL BUREAU OF STANDARDS

NATIONAL BUREAU OF STANDARDS

The National Bureau of Standards [1] was established by an act of Congress March 3, 1901. Today, in addition to serving as the Nation's central measurement laboratory, the Bureau is a principal focal point in the Federal Government for assuring maximum application of the physical and engineering sciences to the advancement of technology in industry and commerce. To this end the Bureau conducts research and provides central national services in four broad program areas. These are: (1) basic measurements and standards, (2) materials measurements and standards, (3) technological measurements and standards, and (4) transfer of technology.

The Bureau comprises the Institute for Basic Standards, the Institute for Materials Research, the Institute for Applied Technology, the Center for Radiation Research, the Center for Computer Sciences and Technology, and the Office for Information Programs.

THE INSTITUTE FOR BASIC STANDARDS provides the central basis within the United States of a complete and consistent system of physical measurement; coordinates that system with measurement systems of other nations; and furnishes essential services leading to accurate and uniform physical measurements throughout the Nation's scientific community, industry, and commerce. The Institute consists of an Office of Measurement Services and the following technical divisions:

Applied Mathematics—Electricity—Metrology—Mechanics—Heat—Atomic and Molecular Physics—Radio Physics [2]—Radio Engineering [2]—Time and Frequency [2]—Astrophysics [2]—Cryogenics.[2]

THE INSTITUTE FOR MATERIALS RESEARCH conducts materials research leading to improved methods of measurement standards, and data on the properties of well-characterized materials needed by industry, commerce, educational institutions, and Government; develops, produces, and distributes standard reference materials; relates the physical and chemical properties of materials to their behavior and their interaction with their environments; and provides advisory and research services to other Government agencies. The Institute consists of an Office of Standard Reference Materials and the following divisions:

Analytical Chemistry—Polymers—Metallurgy—Inorganic Materials—Physical Chemistry.

THE INSTITUTE FOR APPLIED TECHNOLOGY provides technical services to promote the use of available technology and to facilitate technological innovation in industry and Government; cooperates with public and private organizations in the development of technological standards, and test methodologies; and provides advisory and research services for Federal, state, and local government agencies. The Institute consists of the following technical divisions and offices:

Engineering Standards—Weights and Measures — Invention and Innovation — Vehicle Systems Research—Product Evaluation—Building Research—Instrument Shops—Measurement Engineering—Electronic Technology—Technical Analysis.

THE CENTER FOR RADIATION RESEARCH engages in research, measurement, and application of radiation to the solution of Bureau mission problems and the problems of other agencies and institutions. The Center consists of the following divisions:

Reactor Radiation—Linac Radiation—Nuclear Radiation—Applied Radiation.

THE CENTER FOR COMPUTER SCIENCES AND TECHNOLOGY conducts research and provides technical services designed to aid Government agencies in the selection, acquisition, and effective use of automatic data processing equipment; and serves as the principal focus for the development of Federal standards for automatic data processing equipment, techniques, and computer languages. The Center consists of the following offices and divisions:

Information Processing Standards—Computer Information — Computer Services — Systems Development—Information Processing Technology.

THE OFFICE FOR INFORMATION PROGRAMS promotes optimum dissemination and accessibility of scientific information generated within NBS and other agencies of the Federal government; promotes the development of the National Standard Reference Data System and a system of information analysis centers dealing with the broader aspects of the National Measurement System; and provides appropriate services to ensure that the NBS staff has optimum accessibility to the scientific information of the world. The Office consists of the following organizational units:

Office of Standard Reference Data—Clearinghouse for Federal Scientific and Technical Information [3]—Office of Technical Information and Publications—Library—Office of Public Information—Office of International Relations.

---

[1] Headquarters and Laboratories at Gaithersburg, Maryland, unless otherwise noted; mailing address Washington, D.C. 20234.
[2] Located at Boulder, Colorado 80302.
[3] Located at 5285 Port Royal Road, Springfield, Virginia 22151.

UNITED STATES DEPARTMENT OF COMMERCE
Maurice H. Stans, Secretary
NATIONAL BUREAU OF STANDARDS • Lewis M. Branscomb, Director

TECHNICAL NOTE 499

ISSUED OCTOBER 1969

Nat. Bur. Stand. (U.S.), Tech. Note 499, 68 pages (Oct. 1969)
CODEN: NBTNA

Multiple Scattering Corrections for the Associated-Particle Neutron Time-of-Flight Technique

Allan C. B. Richardson*

Nuclear Radiation Division
Center for Radiation Research
National Bureau of Standards
Washington, D.C. 20234

*The author's present address is:
Office of Grants Administration, Environmental Control Administration, Department of Health, Education, and Welfare, Washington, D.C., 20203.

For sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402
(Order by SD Catalog No. C13.46:499), Price 65 cents.

Abstract

The computer code, MAGGIE, for the calculation of multiple scattering and sample attenuation in neutron differential cross-section measurements, has been revised and corrected. The particular case of the scattering geometry required by the associted-particle time-of-flight is considered in detail.

Key words: associated-particle, cross-section, Monte Carlo, multiple scattering, neutron, time-of-flight

MULTIPLE SCATTERING CORRECTIONS FOR THE ASSOCIATED-PARTICLE NEUTRON TIME-OF-FLIGHT TECHNIQUE

Allan C. B. Richardson

I. INTRODUCTION

Measurements of fast neutron elastic and inelastic differential cross sections have, for many years now, usually been done using one of two time-of-flight techniques. The first of these requires a pulsed source of neutrons, and energy separation of the various neutron groups is then achieved by time correlation of the scattered neutrons with the incident neutron pulse. This technique has the advantage of flexibility of incident neutron energy and intensity, and the disadvantages of a relatively high time-correlated background and a low duty cycle. The other, and less commonly used, technique utilizes the detection of a charged particle from the neutron source reaction to tag the incident neutrons in time and direction. Energy separation of the various scattered neutron groups is then achieved by time correlation with the incident neutrons. This "associated-particle technique" has the advantages of very small time-correlated background, inherent absolute determination of the incident correlated neutron flux, and high duty cycle; but it suffers from limitations on the available neutron intensity and energy. However, at energies and intensities where this technique is applicable, it is the method of choice, since it is capable of yielding results of high accuracy without the ambiguities introduced by the time-correlated backgrounds and the massive shielding required by pulsed source techniques. The source reactions eligible for this method are those involving very light nuclei, and therefore capable of producing a light (and thus energetic) stable recoil nucleus. The $T(d,n)^4He$ reaction, producing 14-15 MeV neutrons at 90° over a rather wide range of incident particle energies, is most commonly used; other reactions that have been employed are $D(d,n)^3He$ and $T(p,n)^3He$, both of which produce lower energy neutrons. We will confine the discussion here to the $T(d,n)^4He$ case, although the method described is more generally applicable.

The associated-particle technique has scattering sample requirements that are quite different from those for a pulsed source. Instead of a relatively uniform incident neutron flux across the sample, the correlated neutron beam is highly directional. The angular distribution about the neutron beam line is usually well approximated by

$$I = I_o e^{-\left(\frac{\theta}{\theta_o}\right)^2},$$

with θ_o typically only a few degrees [1]. This property can be very useful [2]. It provides a high degree of neutron collimation without the need for massive collimators, which, in the case of 14 MeV neutrons, can produce substantial degradation of the initially monoenergetic neutron

beam. However, it forces the use of scattering samples of uniform thickness so that the cylindrical or spherical samples commonly used to simplify multiple scattering corrections are immediately ruled out. Otherwise a detailed knowledge of the neutron beam shape and extremely accurate alignment of this beam with respect to the scattering sample is needed. This alignment problem is further complicated because the center of the neutron beam slowly moves back as the neutron producing target ages with use. In measuring angular distributions of scattered neutrons it is of course also desirable to reduce the amount of scattering sample not directly in the neutron beam, so as to minimize multiple scattering.

A scattering sample in the form of a truncated cone, axis lying along the neutron beam, best satisfies all of these requirements. The origin of this cone is taken sufficiently far behind the source to allow for finite spot size on the neutron producing target, to provide some flexibility in alignment, and also to make allowance for changes due to target aging during a run. In order to make best use of the available neutron intensity, one must also use the thickest sample possible. The limit is set by either the angular resolution required at 90° or the time resolution required. A typical geometry is shown in figure 1.

In either case the resulting samples are sufficiently thick to require a careful multiple scattering correction. None of the analytical techniques [3], useful at energies up to a few MeV, are adequate at 14 MeV, the energy most commonly used for measurements of this type, since at energies above 6-7 MeV the diffraction peaks in the elastic angular distributions become too numerous. The only method of sufficient generality is the Monte Carlo technique. A survey of existing Monte Carlo codes revealed none for this particular geometry, but it was immediately apparent that the code "MAGGIE," developed by Parker, Towle, Sams, et al. at Aldermaston [4,5] contained all of the other elements important to such a calculation. For example, this code easily accommodates the neutron source distribution specified above. In addition, MAGGIE calculates an energy spectrum at each angle, so that false peaks due to double scattering can easily be identified. This sophistication is often useful, for example: the measurement of inelastic scattering from the very weakly excited 7.66 MeV 0^+ level in ^{12}C is easily confused by double scattering from the more easily excited 4.43 MeV 2^+ level in this nucleus.

A corollary need of any Monte Carlo neutronic calculation is an easily accessible, but at the same time sufficiently general, file program for the nuclear data required. This was available in a companion code to MAGGIE, entitled MOULD [6]. We have therefore modified the code MAGGIE so that it now handles the geometry required for associated-particle time-of-flight measurements. During the course of this modification we also corrected a few coding errors found in the original version, and made several additional modifications, principally updating the code to current computer syntax and capabilities.



Fig. 1. The experimental geometry for associated-particle measurements at 14 MeV. The associated neutron intensity profile is indicated at the bottom of the figure.

Although a complete description of the code would be out of place here (see references 4 and 5 for details), a general overview of the program will facilitate later discussion of specific details. The point of view adopted is first to sample the scattering sample geometry and the available nuclear interactions using straightforward Monte Carlo techniques. Then, at each collision point, the weighted probability of scattering and escape to each of 33 detector positions (angles) in a half-plane lying to one side of the neutron beam axis is computed using the experimental data for elastic events and each of those inelastic processes of interest. The use of weighted probabilities of scattering to each of the detector positions at the final collision in the sample in place of a completely Monte Carlo approach results in a greatly reduced computation time. This is because the small solid angle subtended by each of the detectors (typically 10^{-3}) makes a final Monte Carlo scattering particularly inefficient. The output angular distributions obtained from applying this procedure to, typically, 1000 interacting neutrons are then reflected about the experimental input data and used as input for a second iteration. Two or three iterations are usually sufficient to obtain a convergent result.

In section II we give a description of the changes made in the code. First, the new coding for the scattering geometry used in the associated particle technique is described. Next we discuss a number of coding errors in the original version. Finally some changes are described that simplify the code and adopt it to FORTRAN V syntax. In section III we give some results obtained using data from the scattering of 14 MeV neutrons on natural carbon. A listing of those subroutines entirely rewritten or having extensive changes is given in Appendix A. In figure 2 the calling sequence for all of the components of the program is shown. A brief description of all of these subroutines appears in Appendix B.

II. DESCRIPTION OF MODIFICATIONS TO THE MONTE CARLO CODE MAGGIE

A. Changes Due to the New Scattering Sample Shape

Four subroutines are affected by changing the shape of the scattering sample. These are: 1) subroutine INPUT - those sections where scatterer parameters are read in and the flux attenuation factor is calculated are affected. The flux attenuation factor is defined as the ratio of incident flux along the axis of the sample to average flux in the entire sample. 2) CRNEU, the subroutine that creates incident neutrons at the entrance face of the scatterer by random sampling of the incident neutron spatial distribution. 3) TRACK, the tracking subroutine. 4) FPATH, the subroutine for calculating the probability of neutron escape from the sample in the direction of each of the assumed detector positions, for each collision point arrived at in TRACK.

It is worth noting here, although not necessary to what follows, that the data used for a) the neutron track lengths in the Monte Carlo sampling of the sample shape from subroutine EGMV, and b) the Monte Carlo sampling of reaction type and angular distribution at each collision by subroutine



Fig. 2. The calling hierachy for the present version of code MAGGIE.

CR, as well as c) the transmission probabilities in the direction of the detectors used in subroutines FPATH and NAPAN, are all drawn from the MOULD nuclear data file tape and not from input experimental data. The only experimental data employed are angular distributions used for the calculation of the scores for the relative probability of scattering to the various assumed detector positions in subroutine NAPAN. The elastic angular distribution (for the incident neutron energy only) used here is also automatically updated after each iteration by the subroutine AUTO. Thus it may be necessary to update the angular distributions on the MOULD file tape before and during the course of data-processing.

We now describe the changes due to the new scattering geometry in some detail for each of the subroutines affected.

1. INPUT

a. Cards 0207-0226 are changed to eliminate parameters required for samples consisting of concentric cylindrical shells, with common axes perpendicular to the beam axis, and to substitute those needed to characterize a truncated cone sample, axis lying along the neutron beam, and origin behind the neutron source. The new variables are HITE, FRAD, and ANGLE; the height, entrance face radius, and half-angle of the sample, respectively. HITE is immediately redefined as HITE/2, a more convenient quantity in subsequent calculations.

b. Card 0245, the calculation of the maximum angle subtended by the scattering sample at the neutron source, is changed to conform to the new geometry.

c. Cards 0301-0303 have been replaced. The correct expression for the flux attenuation factor for the new geometry is

$$\frac{F_o}{F} = \frac{K(o)}{\overline{K}} \cdot \frac{C}{N\lambda} \cdot \frac{h(r_1^2 + r_1 \Delta r + \Delta r^2/3)}{(1-\cos\theta_m)\, d^2} \quad ,$$

where h is the half-length of the scattering sample, r_1 the radius of its entrance face, Δr the difference in radii of the entrance and exit faces, and d the distance from the source to the entrance face of the sample. The remaining symbols are defined as in the original.

d. The original version of MAGGIE utilized a sample which was not symmetric about the axis of the incident neutron flux. Thus the experimental sampling of scattered neutrons in the detector plane was not truly representative of the scattering into 4π, which is employed in the program to calculate the flux attenuation factors and which are used in turn to infer the integrated cross-sections. This necessitated a small correction which was calculated with the help of a classification of the outgoing

Monte Carlo tracks vs. energy and the angle with respect to the scattering sample axis. Since the present scattering sample is symmetric about the incident neutron flux the experimental sampling of scattered neutrons in the detector plane is representative, and no correction is required. Accordingly, cards 0331-0338 in INPUT, cards 1544-1548 in DATIN, and cards 1735-1743 in MAGGIE are deleted. Card 1734 of MAGGIE is replaced by the statement

```
20 CONTINUE
```

The output of this table, by cards 3695-3715 of subroutine OUTB3, is also deleted.

2. CRNEU

Cards 3117-3119, 3140-3141, 3143-3147 and 3151 are replaced as shown in the listing. The new coding creates neutrons randomly scattered over the face of the conical scattering sample, in accordance with the specified spatial distribution. The old reference to multiple materials is not deleted, but the sample is now designated "material one." Similarly, the register containing neutrons which miss the sample is retained, although for this geometry misses occur with very low frequency.

3. TRACK

The entire subroutine has been replaced. The geometry is illustrated in figure 3. The subroutine is entered with the starting point (x_o, y_o, z_o) and the direction cosines $(\cos\theta_x, \cos\theta_y, \cos\theta_z)$ already defined. A random sampling of the neutron mean free path establishes the track length to the next possible collision. The track vector is then extended until it intersects the plane determined by the endface of the sample in the direction of travel of the neutron, and the path length from the starting point to this intersection is computed. A comparison of this intersection point with the radius of the endface establishes whether the track is in the direction of the endface or the curved surface of the sample, and the program branches accordingly. If the track passes through the endface, the path length calculated above is compared with the Monte Carlo track length to the next collision and the coordinates of collision or escape from the surface of the sample as well as the time elapsed along the track are computed in a straight-forward way.

We consider now the procedure used for a neutron headed toward a curved surface of the scattering sample. The coordinates of the endpoint of the previously determined Monte Carlo track length are first found. These are used to calculate the projected distance, perpendicular to the symmetry axis, of this endpoint from the symmetry axis, as well as the length of the radius of the sample lying along this projection. Comparison of these quantities determines whether a collision occurs within the sample or not. If so, the coordinates are already known and the time elapsed along the track is all that remains to be calculated. If not, it is necessary to calculate the coordinates of the neutron's exit from



Fig. 3. The geometry for subroutine TRACK. The trajectory shown is that of a neutron which, after collision at point x_o, y_o, z_o escapes from the curved surface of the sample at point x, y, z.

the surface of the cone. Designate ℓ the path length to the surface and x, y, z the coordinates of the intersection of the track with the surface. We have, referring to figure 3,

$$x - x_o = \ell\cos\theta_x$$

$$y - y_o = \ell\cos\theta_y$$

$$z - z_o = \ell\cos\theta_z \quad ,$$

so that the projected distance, r, from the symmetry axis of the cone to the point (x, y, z) is given by

$$r^2 = y^2 + z^2$$

$$= \ell^2 \sin^2\theta_x + 2\ell(y_o\cos\theta_y + z_o\cos\theta_z) + y_o^2 + z_o^2 \quad , \qquad (1)$$

where we have used the identity

$$\cos^2\theta_x + \cos^2\theta_y + \cos^2\theta_z = 1 \ .$$

Since we know the parameters of the cone we can also calculate r from the x coordinate (again see figure 3.):

$$r = r_1 + (h+x)\tan\theta_o \quad , \qquad (2)$$

where θ_o is the half-angle of the cone. Eliminating r from eq'ns. (1) and (2) and arranging the terms as a quadratic in ℓ, we obtain

$$\ell^2\left[1-\cos^2\theta_x(1+\tan^2\theta_o)\right]$$

$$+ 2\ell\left[y_o\cos\theta_y + z_o\cos\theta_z - \cos\theta_x(r_1\tan\theta_o + h + x_o)\tan^2\theta_o\right]$$

$$+ \left[y_o^2 + z_o^2 - (r_1 + (h+x_o)\tan\theta_o)^2\right] = 0. \qquad (3)$$

The positive root of this equation is the required path length to the surface, and the subroutine FONEC is then called to provide the x, y, and



Fig. 4. Subroutine TRACK. The subroutines EGMV and FONEC return the neutron mean free path and the coordinates at the end of a track, respectively. RANDA returns a random number.

z coordinates. Error prints are provided for the cases of two positive, two negative, imaginary, or indeterminate roots as solutions to eq. (3). However none of these situations has occurred in many tens of thousands of tracks, although at least some of them are mathematically possible. Once ℓ has been calculated, determination of the coordinates of escape and the track time are straightforward. The subroutine also returns an index that indicates the fate of the neutron, i.e., curved escape, plane escape, or collision. A block diagram is shown on figure 4.

4. FPATH

This subroutine has also been entirely replaced. The same simplifying assumption is made as in the original coding--that is, the dimensions of the scattering sample are considered to be negligible compared to the flight path to the detector. This has the effect that the angle and flight path to any particular detector position may be considered to be the same from any scattering point in the sample. The quantities to be calculated are the neutron path length, p, in the sample from any point (x, y, z) to the surface of the sample and the scattering angle, θ_d, in the direction of a particular detector, at the angle ψ. The geometry is shown in figures 5 and 6. All paths are assumed to be parallel to the x-y plane, and all detector positions satisfy the condition $y \geq 0$.

We note that the locus of the intersection of a cone with a plane parallel to its axis is an hyperbola, and write, using the notation shown in figure 5,

$$\frac{X^2}{a^2} - \frac{Y^2}{b^2} = 1 \quad ,$$

$$\text{or} \qquad Y^2 = X^2 \tan^2\theta - z \quad , \tag{4}$$

$$\text{since} \qquad b = z \quad \text{and} \quad a = z/\tan\theta .$$

Now, referring to figure 6, we may also write

$$Y = p \sin\psi + y$$

$$\text{and} \qquad X = p \cos\psi + x' \quad , \tag{5}$$

$$\text{where} \qquad x' = R + h + x = \frac{r_1}{\tan\theta} + h + x .$$

Again we reduce the problem to a quadratic in path length, p, after



Fig. 5. The geometry for subroutine FPATH. The plane of forced scattering is located at a height $r_1<z<r_2$ in this instance. The track of the incident neutron does not, in general, lie in this plane as shown.



Fig. 6. A section through the scattering sample at height $z<r_1$. The upper case quantities refer to the axes X and Y, whose origin is that of hyperbola defined by the intersection of the plane (x,y) with the surface of the scattering sample.

combining eq's (4) and (5) to eliminate the variables X and Y to obtain:

$$p^2(\sin^2\psi-\cos^2\psi\tan^2\theta)$$

$$+ 2p(y\sin\psi-x'\cos\psi\tan^2\theta)$$

$$+ (y^2-x'^2\tan^2\theta+z^2) = 0 \ . \qquad (6)$$

For each value of z there will be a pair of angles, α and β (see figure 6 , which define the limits of the hyperbolic curve. These angles are given by

$$\tan\alpha = \frac{(r_1^2-z^2)^{1/2}-y}{h+x}$$

$$\tan\beta = \frac{(r_2^2-z^2)^{1/2}-y}{h-x} \ . \qquad (7)$$

The subroutine is diagrammed in figure 7. After testing for the special case of exit perpendicular to the beam axis, the program tests, using eq's (7), for exit through the endfaces vs. the curved sides for the exit angle, ψ, and branches accordingly. The path length in the former case is a straightforward calculation, and for curved escape is the positive root of eq. (6). It should be noted that in the limiting case of cylinder ($\tan\theta=0$) this subroutine, unlike all of the others, does not work. A modified subroutine for a cylindrical sample is given in the Appendix following the listing of FPATH for a truncated cone.

B. Correction of Coding Errors [7]

1. INPUT

a. Statements resulting in LGR=0 in the table look-up for the mean free path (following card 0308) have all been changed to give LGR=1. LGR=0 references not a mean free path, but instead the last tabular value of collision probability in the previous MOULD table. The revised look-up supplies the mean free path at the lowest tabulated energy for any neutron at or below that energy.

b. On the card following statement 5001, LRG has been replaced by the correct variable, LGR.

c. Card 0441 is replaced by

IMINM = IMAXM+1 .

This change yields sequential storage of supplementary ranges of experimental angular distributions, and thus avoids loss of needed storage space in the array SUPVAL (I,J).



Fig. 7. Subroutine FPATH, for a truncated cone. The subroutine for a cylinder is similar.

2. EGMV

LGROUP=0 has been eliminated for the reason given in 1a. above.

3. NAPAN

a. The angle used for the interpolation of the experimental distributions, as well as for calculation of the neutron energy after collision is the laboratory angle, calculated in the subroutine FPATH. For this reason the experimental angular distributions must be read in at laboratory angles. Also the center-of-mass energy calculation on cards 3494 and 3497-3501 (in the case of center-of-mass MOULD angular distribution tables) is in error. This has been changed to a calculation in laboratory coordinates by replacing card 3494 by

```
      GO TO (36,11,11,11,11,11,11,11,36,11,11,11,11,11,11,11) NFORM
```

and deleting cards 3497-3501.

b. The sequence of cards 3502-3512, which picks the appropriate experimental angular distribution values, does not refer to the correct angular distributions, nor to the correct neutron energy--that before collision. It has been replaced by the sequence:

```
11      IF(IMAX(J).LE.0) GO TO 15
        IMINM=IMIN(J)
        IMAXM=IMINM+IMAX(J)-1
        DO 50 JJ=IMINM,IMAXM
        IF(EIN-ENVAL(J,JJ))50,51,52
50      CONTINUE
51      KK=JJ
        GO TO 19
52      IF(JJ.LE.IMINM) GO TO 15
        KK=JJ-1
```

c. On the card following statement 5001, LRG has been replaced by the correct variable, LGR.

d. LGR=0 has been eliminated for the reason given in 1a. above.

e. The option that provides for suppression of printout of various scores, through setting the indicators IANALA, IANALB, IANALC, and IANALD negative, should not suppress storage of these scores by NAPAN. The time saved is negligible and the elastic scores, DEB(I,L), are required by the automatic iteration scheme, AUTO. Cards 3528-43 have been revised to eliminate the dependence on these printout indicators.

4. ABSYND

LGROUP=0 has been eliminated for the reason given in 1a. above.

5. CREN

For the same reason set out in section 3a. above, the center-of-mass energy calculation (cards 2960-66) has been replaced by a calculation in laboratory coordinates by deleting cards 2961-66 and replacing card 2960 with

880 GO TO 800 .

6. OUTPUT, OUTB3, OUTB4

The sum over energy, at each detector angle, stored in the vector DES(J,33) is required by subroutine AUTO. So as to allow calculation of this quantity in subroutine OUTB4, even when no B4 printout is requested, a print indicator, IFPR, has been added to the call for subroutine OUTB4. This is accomplished by the changes shown in the listing for cards 3721, 3808A, 3873, and 3975-4002.

7. AUTO

a. The quantity "chi-squared," on card 2084, should be

$$\chi^2 = \sum_{1}^{33} \frac{\left(\sigma(\theta)_{exp} - \sigma(\theta)_{calc}\right)^2}{\sigma(\theta)_{exp}} \quad ,$$

and not as formerly written, with the denominator squared.

b. It should be noted that the normalization of the Monte Carlo output on cards 2065-2068 and 2088 is not, in general, correct; but only holds for detectors positioned at equal increments of $\cos\theta$ between -1 and +1. For this reason, if subroutine AUTO is used, the input detector positions must satisfy this criterion.

8. FPATH

The original version of this subroutine contained two errors. These do not apply to the new version of FPATH reported here, but are listed for completeness. Card 3356 of the original should read

SINOM = SQRT(1-COSOM**2) ,

card 3358 be deleted, and a new card inserted following card 3359:

FP1 = WORK16**2+WORK17**2-FP2**2 .

C. Other Modifications

1. General

a. Common storage assignments have been handled by combining all common statements into one package, processed by the UNIVAC 1108 "Procedure Definition Processor" using the assembler directive FCOPY (Fortran copy). This package, designated CINC1, is then included at the time of assembly in all subroutines making use of common variables by means of the statement

INCLUDE CINC1

placed immediately following the subroutine name definition. This process, which effects a considerable economy in the size of the source deck and listing, is characteristic of the UNIVAC 1108 Assembler and FORTRAN V; however, equivalent procedures are often available to other systems. In some subroutines dimension statements still appear for those few variables not in common storage. A block of common storage has been specifically assigned to the subroutine ABSYND variables DATA and IDATA. This carries the dummy label BLANK. The details of these changes in memory storage allotment will be obvious upon examination of the listings.

b. The size of many modern computers obviates the need for linkage. We have deleted references to CHAIN(I,J) and incorporated the balance of subroutine PRELUDE into the main program MAGGIE. Similarly, references to CHAIN(I,J) in subroutines DATIN and AUTO have been replaced by the appropriate CALL and/or RETURN statements.

c. The final F in the names of all library functions (such as SIN, COS, EXP, MIN) has been deleted, as it is not compatible with FORTRAN V. In addition, such functions as FLOAT and INT have been eliminated by using the mixed expressions allowed by FORTRAN V.

d. Disc storage read and write statements have been modified in the main program MAGGIE and subroutine WRTBT to conform to 1108 FORTRAN V usage.

e. A number of formats have been altered. Some of the changes are merely different spacing options, but others are required by the new scattering geometry. A list of card numbers of the affected statements follows:

0226	0226A	0226B
0249	0258	0345
0410	0450	0451
1719	1963	1972
2111	2115	3638
3639	3828	3833

On card 2735 in subroutine CR the variable N has been replaced by the correct variable NSECS.

f. A new random number generator, subroutine RANDOM, entry RDM, has been incorporated, and the required changes in the functions RANDA and NRANDA are shown in the listings.

2. MAGGIE

a. All of the subroutine PRELUDE, except for calls to subroutines CLOCK and CHAIN, has been inserted following card 1654. A call to subroutine RANDOM immediately following the read-in of OCT, the starting value of the random number generator, initializes this generator. OCT is printed out following the call to subroutine INPUT.

b. All references to subroutine CLOCK have been deleted.

c. Card 0530 is eliminated by changing cards 1776, 1778, 1787, 1789, and 1792 to read

GO TO 1 .

3. ABSYND

a. Card 0525, which assigns the logical tape unit carrying the MOULD nuclear data tape, now reads

NUCDAT=9 .

On cards 0525, 0530, and 1394 the variable name TAPE has been changed to ATAPE to avoid confusing the compiler. These changes may not be required by other installations.

b. Cards 0553 and 0554 set all storage for the variables DATA and IDATA to zero before each ABSYND run.

c. Card 1398 is modified so as to print only those action numbers processed.

4. CR

The variable names NACT and Q have been changed to NACTV and QV, so as to avoid conflict with the array names NACT(I) and Q(I). Similarly, the variable name COS is changed to COZ, so as to make the library function COS available.

5. CREN

a. The variable names NACT and Q have been changed to NACTV and QV, for the reason given above.

b. Cards 2832-2837, 2878-2881, and 2911-2915 have been deleted, since they are not needed. In order to accomodate these deletions card 2910

has been amended to read

```
IF(NVCOS.LT.1) GO TO 208        ,
```

and card 2916 to read

```
P = (AS+SQRT(AS**2+A*QV*(1+A)/EIN+A**2-1))/(1+A) .
```

6. AUTO

a. The multiple elastic sums are not required, and so cards 2069-2072 are deleted.

b. The quantity RATIO is not used, and has been eliminated from cards 2077 and 2078.

c. The do-loop 2083-2085 is redundant, since ELM2(J) is also set at card 2097. Cards 2083-2085 are therefore deleted, and card 2080 is modified to reflect this change.

d. The three do-loops in the sequence 2087-2098 have been combined into a single loop.

e. The variable name EXP(J) has been changed to EZP(J) to avoid conflict with the library function EXP.

f. Often it is desirable to separate an iteration procedure into two or more consecutive runs. Cards 2073-2082 have been modified to allow a run to be made using the partially corrected output of a previous run as input, instead of the experimental data. When this option is to be used the second field of the input card specifying the number of iterations, NTERM, should be non-zero. This is then followed by the cards specifying the experimental values for the angular distribution, FCVAL, which are removed from their usual position and replaced by the partially corrected output of the previous run.

g. In the case of rapidly varying angular distributions such as at 14.1 MeV, the usual iteration procedure is not as rapidly convergent as the "physical" method. For this method the calculated multiple scattering is first subtracted from the experimental input, and then the balance of the iteration (sample attenuation) is performed as usual by reflecting the output for single scattered neutrons about the input. The new coding on cards 2091-2097 reflects this change. For the first two iterations the iteration improves only the multiple scattering, the correction being applied both times to the experimental input. After two iterations multiple scattering is well enough known to allow the iterative procedure full play, so the correction is applied each time to the previous input, instead of the experimental values. This procedure yields much more rapid convergence, three iterations providing better convergence than six of the previous method.

III. AN APPLICATION TO 14.1 MeV NEUTRON SCATTERING

The code has been applied to a typical associated-particle scattering geometry for 14.1 MeV neutrons on carbon. The scattering sample was a truncated cone of half-angle seven degrees, length 3.193 cm., and entrance face radius 2.059 cm., with its center located 20 cm from the neutron source. The experimental input used was simulated using published results for carbon at this energy. The results of a typical run are shown in Table 1, and on figures 8 and 10. The cross-section data used for the Monte Carlo scattering were those of Slaggie and Reynolds [8]. In Table 1 the quantity $\sigma(\theta)$ represents the true angular distribution, and the total and multiple outputs are the results calculated using it and the specified sample shape. The code varies $\sigma(\theta)$ until the total elastic output matches the experimental input to the accuracy required. The calculated angular distribution for neutrons undergoing multiple scattering is shown in figure 8. It can be seen that the result converges quite rapidly. Further iterations resulted only in statistical variations about the values obtained after three iterations; in fact, the largest change after two iterations, that at $\cos\theta = 0.625$, represents only a 1.5% change in the cross section.

In figure 9 we show the part of the correction, exclusive of multiple scattering, that depends upon sample shape. Also displayed for comparison is a calculation of the effect expected due to attenuation in the sample for an isotropic angular distribution. As can be seen, this correction is not independent of the input angular distribution. The quantity plotted, $\Delta\sigma/\sigma$, is the difference between the singly scattered output and the input, divided by the input, for each angle. This geometrical correction is contributed to about equally by varying path length in the sample and the change in the total neutron cross section with energy as a function of the neutron scattering angle. The correction varies from a few percent to about ten percent, and is directly dependent upon the accuracy with which the total neutron cross section is known over the range of energy exhibited by the neutron recoil. On the other hand, the correction for multiple scattering is larger, ranging from about 50% at the backward minimum to 4% at zero degrees, but depends mainly upon the experimental input data. Over most of the practical angular range of measurement it is a quite appreciable 15-20%. Figure 10 shows the input distribution used and the corrected output distribution obtained after three iterations of approximately 2000 interacting neutrons each. The total correction is, of course, largest in regions where the cross section exhibits minima. It varies from a few percent to a maximum of only twenty percent at measurable angles, since the geometrical and multiple scattering corrections tend to be in opposite directions, except at the extreme backward angles. Several examples of spectra showing elastic-inelastic and multiple inelastic effects in the energy spectra are given in the original references [4, 5]; the present version of MAGGIE also yields similar results.

TABLE 1

The scores for a typical Monte Carlo run for carbon at 14.1 MeV.

COUNTER NUMBER	Cos θ	σ(θ)	TOTAL ELASTIC OUTPUT	MULTIPLE ELASTIC OUTPUT	EXPERIMENTAL INPUT
1	-1.0000	.023	.044	.021	.044
2	- .9375	.075	.092	.022	.093
3	- .8750	.093	.111	.024	.111
4	- .8125	.100	.120	.026	.121
5	- .7500	.110	.131	.028	.131
6	- .6875	.127	.148	.030	.148
7	- .6250	.152	.170	.031	.171
8	- .5625	.176	.190	.033	.191
9	- .5000	.202	.212	.034	.212
10	- .4375	.225	.231	.035	.232
11	- .3750	.240	.246	.036	.246
12	- .3125	.248	.253	.037	.254
13	- .2500	.245	.251	.037	.251
14	- .1875	.233	.240	.038	.241
15	- .1250	.216	.225	.038	.226
16	- .0625	.192	.205	.038	.205
17	.0000	.173	.183	.038	.183
18	.0625	.145	.155	.037	.155
19	.1250	.125	.135	.037	.135
20	.1875	.114	.125	.037	.125
21	.2500	.107	.123	.039	.122
22	.3125	.110	.127	.041	.126
23	.3750	.124	.142	.044	.140
24	.4375	.154	.170	.049	.167
25	.5000	.203	.215	.055	.212
26	.5625	.281	.285	.063	.281
27	.6250	.412	.404	.074	.400
28	.6875	.628	.605	.087	.600
29	.7500	.969	.929	.104	.925
30	.8125	1.486	1.435	.125	1.435
31	.8750	2.274	2.218	.151	2.219
32	.9375	3.451	3.380	.181	3.387
33	1.0000	5.197	5.045	.216	5.062



Fig. 8. The angular distribution of multiply scattered neutrons on carbon at 14.1 MeV for two successive iterations. The data for the third iteration are also given in Table 1, after suitable normalization.



Fig. 9. The correction due to sample shape. The quantity $\Delta\sigma/\sigma$ is the change in the normalized angular distribution after subtracting multiple scattering.



Fig. 10. The experimental input and corrected output for carbon at 14 MeV.

REFERENCES

1. Monier, L. F. C., Tripard, G. E., and White, B. L., Nucl. Instr. and Meth. 45, 282 (1966).

2. Marshak, H., Richardson, A. C. B., and Tamura, T., Phys. Rev. 150, 996 (1966).

3. A useful summary is given by M. Walt in Fast Neutron Physics, Vol. II, Marion, J. B., and Fowler, J. L., Ed. (1960).

4. Parker, J. B., Towle, J. H., Sams, D., and Jones, P. G., Nucl. Instr. and Meth. 14, 1 (1961).

5. Parker, J. B., et al, Nucl. Instr. and Meth. 30, 77 (1964).

6. Parker, K., AWRE report O-70/63; Kerr, W. M. M., AWRE report O-81/64 (1964); Miller, S. M., and Parker, K., AWRE report O-55/65.

7. Some of these coding errors have also been previously noted in private communications. We are indebted to J. B. Parker, Aldermaston, for noting the substitution of REDEN for EIN in subroutine NAPAN, as well as the errors in subroutine FPATH. H. Horstmann and H. Schmid, Geel, have noted, in addition, the difficulty involving the center of mass calculation of neutron recoil energy in subroutines NAPAN and CREN.

8. Slaggie, E. L., and Reynolds, J. T., KAPL-3099, (1966).

APPENDIX A

Listings of new and extensively revised coding.

A complete listing is available by request from the Center for Radiation Research, Neutron Physics Section, National Bureau of Standards, Washington, D. C. 20234.

```
CINC1* FCOPY                                                                    NBS
C                                                                               EU.
C       COMMON STORAGE ALLOCATION.                                              EU.
C                                                                               EU.
       COMMON LOC,OCT                                                           NBS
       DIMENSION DATA(1),IDATA(1)                                               EU.
       EQUIVALENCE (DATA,IDATA)                                                 EU.
       COMMON IDATA,INIT,NEGS,UMAX,XLYMIN,IXMAT,IDICE,NMATS,EMC(257),           NBS
      1        PATH,SPEED,MAT,EIN,UIN,LGROUP,ROOTE,WIN,WOUT,NSECS,              NBS
      2        COSPHI(100),EOUT(100),UOUT(100),ISORAN(100) ,NOLAW(100),         NBS
      3        NONUC(100),NOACT(100),NREACT(100),NORNGE(100),ALF,               NBS
      4        ALFP(20),WMIN,WMAX                                               NBS
C                                                                               EU.
C       MAGGIE NUCLEAR DATA AIDS.                                               EU.
C                                                                               EU.
       COMMON NUCLID,NAC,AS,ENER,NFORM,QV,ATOM1(24),Q(24),PART1(24),            NBS
      1        IXACT1(24),IXNUC1,FNEGS,NUCS,NUCL(24),NACT(24),NAC1(24),         NBS
      2        NANAL,NENSP,NOCOU,NOGR,LAWREV(50),LWNO(50),NLWREV                NBS
C                                                                               EU.
C       BIRTH STORES AND REGISTERS.                                             EU.
C                                                                               EU.
       COMMON BIRTH(5500),IBIRTH(1500)                                          NBS
C                                                                               EU.
C       GENERAL WORK STORES.                                                    EU.
C                                                                               EU.
       COMMON IWORK1,IWORK2,WORK3,WORK4,WORK5,WORK6,WORK7,WORK8,WORK9,          NBS
      1        WORK10,WORK11,WORK12,WORK13,WORK14,WORK15,WORK16,WORK17,          NBS
      2        WORK18,WORK19,ISCOLL                                             NBS
C                                                                               EU.
C       DIMENSIONS ETC.                                                         EU.
C                                                                               EU.
       COMMON HITE,FRAD,BRAD,ANGLE,TANGLE,DIST,STRTE,CNPHI(64),FLTPTH           NBS
C                                                                               EU.
C       CONTROL PARAMETERS.                                                     EU.
C                                                                               EU.
       COMMON IRECRG,IRGRA,IRGRB,JOBFIN,NOSAMP,SAMPLE,ANEUNO,NSENSE,IFB4        NBS
```

```
C                                                                       EU.
C       ANALYSIS AND AIDS TO ANALYSIS.                                  EU.
C                                                                       EU.
      COMMON HEAD(12),ONCOL(31),DEGENE(30),DEGENI(30),EDGEN(30),        NBS
     1       ICOLL(100),AMISS,PESC,CESC,ANOCOL,ALLEL,EVDGEN,FCCOS(33),  NBS
     2       FCCOSD(33),FCER(24,15),FCVAL(24,33),SUPVAL(24,33),         NBS
     3       ENVAL(24,24),IMAX(24),IMIN(24),ENSP(33),COUNT(33),         NBS
     4       TOCOL(5,5),                                DEA(33,33),     NBS
     5       DEB(33,33),DEC(33,33),DED(33,33),IANALA,IANALB,IANALC,     NBS
     6       IANALD,FLUXFT,ALAM(32),ITMAG,ITER,EZP(33),NTERM,SAMP(10)   NBS
C                                                                       NBS
C       ABSYND IDATA AND DATA STORAGE                                   NBS
C                                                                       NBS
      COMMON BLANK(15000)                                               NBS
      END                                                               NBS
```

```
C      MAGGIE 3A                                                          1566
C      20.7.64 A.D.PURNELL                                                1570
C      9.68 MODIFIED NBS VERSION FOR FORTRAN V, A.C.B.RICHARDSON         NBS1570A
C      FOR TRUNCATED CONE SCATTERING SAMPLE, INCLUDING AUTOMATIC ELASTIC NBS1571
C      SCATTERING CALCULATION AND GRAPHS.                                NBS1571A
.
       INCLUDE CINC1                                                     NBS
       DIMENSION LAWTP(100)                                               1653
       ITER=1                                                             1654
       INIT = 16719                                                      NBS
       READ(5,51)OCT                                                     NBS
       CALL RANDOM(OCT)                                                  NBS
    51 FORMAT(O12)                                                       NBS
       READ(5,200)(HEAD(I),I=1,12)                                       NBS
       WRITE(6,200)(HEAD(I),I=1,12)                                      NBS
   200 FORMAT(12A6)                                                      NBS
       CALL DATIN                                                        NBS
       CALL INPUT                                                         1656
       WRITE(6,52)OCT                                                    NBS
    52 FORMAT(55HOTHE STARTING VALUE FOR THE RANDOM NUMBER GENERATOR IS ,NBS
      1O12)                                                              NBS
   103 NOSAMP=0                                                           1658
       IRECRG=0                                                           1659
       IRGRA=0                                                            1660
       IRGRB=0                                                            1661
       ANEUNO=0.0                                                         1662
       THERM=0.25000001E-7                                                1663
 1     IF(IRGRA)2,7,4                                                     1664
 2     PRINT 3,ANEUNO                                                     1665
 3     FORMAT(1H1,47HERROR CONDITION-BIRTH REGISTER NEGATIVE ANEUNO=,F6.0  1666
      2)                                                                  1667
       IRGRA=0                                                            1668
       IRGRB=0                                                            1669
       GO TO 7                                                            1670
 4     IRGRA=IRGRA-11                                                     1671
       IRGRB=IRGRB-3                                                      1672
```

```
      IWORK1=IBIRTH(IRGRB+1)                                                    1673
      MAT=IBIRTH(IRGRB+2)                                                       1674
      IWORK2=IBIRTH(IRGRB+3)                                                    1675
      EIN=BIRTH(IRGRA+1)                                                        1676
      WORK3=BIRTH(IRGRA+2)                                                      1677
      WORK4=BIRTH(IRGRA+3)                                                      1678
      WORK5=BIRTH(IRGRA+4)                                                      1679
      WORK6=BIRTH(IRGRA+5)                                                      1680
      WORK7=BIRTH(IRGRA+6)                                                      1681
      WORK8=BIRTH(IRGRA+7)                                                      1682
      WORK19=BIRTH(IRGRA+8)                                                     1683
      UIN=BIRTH(IRGRA+9)                                                        1684
      WIN=BIRTH(IRGRA+10)                                                       1685
      WORK11=BIRTH(IRGRA+11)                                                    1686
      IF(IRGRA-550)13,5,13                                                      1687
5     IF(IRECRG)13,13,6                                                         1688
6     IRECRG=IRECRG-11                                                          1689
      LOC=LOC-5600                                                            NBS1690
      READ(37)IRECRG,(BIRTH(I),I=551,4950),(IBIRTH(I),I=151,1350)             NBS1692
      IRGRA=IRGRA+4400                                                          1693
      IRGRB=IRGRB+1200                                                          1694
      GO TO 13                                                                  1695
7     IF(ANEUNO-SAMPLE)10,8,8                                                   1696
8     NOSAMP=NOSAMP+1                                                           1697
      ANEUNO=0.0                                                                1698
      CALL OUTPUT                                                               1699
      IF(ITMAG-1)81,82,81                                                       1700
  81  IF(NOSAMP-JOBFIN)10,9,9                                                   1701
  82  IF(NAC1(1)-2) 9,84,9                                                      1702
  84  IF(NOCOU-33)9,85,9                                                        1703
  85  CALL AUTO                                                                 1704
      IF(ITER-10) 103,9,9                                                       1705
   9  CONTINUE                                                                NBS1706
      CALL END                                                                  1715
10    CALL CRNEU                                                                1716
      IF(NSENSE)11,13,11                                                        1717
```

```
11    PRINT 12                                                              1718
12    FORMAT(120HOSERIAL  STEP   EN     LETH    WT    L      M      N   NBS1719
     2   X      Y      Z      TIME    FATE  ISO.  ACT.  RAN. LAW  NSECS)   1720
13    IF(NSENSE)14,15,14                                                    1721
14    PRINT                33,ANEUNO,IWORK1,EIN,UIN,WIN,WORK3,WORK4,WORK5   1722
     2,WORK6,WORK7,WORK8,WORK19                                             1723
15    CALL TRACK                                                            1724
      WORK1=WIN                                                             1725
      ISCOLM=ISCOLL                                                         1726
      GO TO (17,16,22),ISCOLM                                               1727
16    PESC=PESC+WORK1                                                       1728
      GO TO 18                                                              1729
17    CESC=CESC+WORK1                                                       1730
18    IF(NSENSE)19,20,19                                                    1731
19    PRINT                34,ANEUNO,IWORK1,EIN,UIN,WIN,WORK3,WORK4,WORK   1732
     25,WORK16,WORK17,WORK18,WORK19,ISCOLM                                  1733
  20  CONTINUE
505   IF(IWORK1)506,506,507                                                 1744
506   ANOCOL=ANOCOL+WORK1                                                   1745
      GO TO 1                                                              NBS1746
 507  IF(IWORK1-1)1,508,509                                                NBS1747
508   I=ICOLL(1)                                                            1748
      ONCOL(I)=ONCOL(I)+WORK1                                               1749
      GO TO 1                                                              NBS1750
509   NOIN=0                                                                1751
      DO 511 I=1,IWORK1                                                     1752
      IF(ICOLL(I)-2)511,511,510                                             1753
510   NOIN=NOIN+1                                                           1754
      LAWTP(NOIN)=LAWTP(I)                                                  1755
511   CONTINUE                                                              1756
      IF(NOIN-2)518,512,518                                                 1757
512   IF(LAWTP(1)-LAWTP(2))513,514,514                                      1758
513   I=LAWTP(2)                                                            1759
      J=LAWTP(1)                                                            1760
      GO TO 515                                                             1761
514   I=LAWTP(1)                                                            1762
```

```
      J=LAWTP(2)                                                        1763
  515 IF(I-5)516,516,518                                                1764
  516 IF(J-5)517,517,518                                                1765
  517 TOCOL(I,J)=TOCOL(I,J)+WORK1                                       1766
  518 IF(ICOLL(1)-2)524,519,519                                         1767
  519 J=ICOLL(1)-1                                                      1768
      NOIN = 0                                                          1769
      DO 521 I=1,IWORK1                                                 1770
      IF(ICOLL(I)-2)521,520,520                                         1771
  520 NOIN=NOIN+1                                                       1772
  521 CONTINUE                                                          1773
      IF(NOIN-1)522,522,523                                             1774
  522 DEGENE(J)=DEGENE(J)+WORK1                                         1775
      GO TO 1                                                          NBS1776
  523 DEGENI(J)=DEGENI(J)+WORK1                                         1777
      GO TO 1                                                          NBS1778
  524 NOIN=0                                                            1779
      DO 526 I=1,IWORK1                                                 1780
      IF(ICOLL(I)-2)526,525,525                                         1781
  525 NOIN=NOIN+1                                                       1782
      NOIN1=ICOLL(I)                                                    1783
  526 CONTINUE                                                          1784
      IF(NOIN-1)527,529,528                                             1785
  527 ALLEL=ALLEL+WORK1                                                 1786
      GO TO 1                                                          NBS1787
  528 EVDGEN=EVDGEN+WORK1                                               1788
      GO TO 1                                                          NBS1789
  529 J=NOIN1-1                                                         1790
      EDGEN(J)=EDGEN(J)+WORK1                                           1791
      GO TO 1                                                          NBS1792
                                                                        1794
C     COLSN                                                             1795
                                                                        1796
   22 IWORK1=IWORK1+1                                                   1797
      CALL CR                                                           1798
      IF(IFB4)23,24,23                                                  1799
```

```
23    CALL CALC                                                    1800
      CALL NAPAN                                                   1801
24    WORK1=WOUT                                                   1802
      IF(IWORK1-100)25,25,26                                       1803
25    IF(NREACT(1)-2)532,531,532                                   1804
531   ICOLL(IWORK1)=1                                              1805
      IF(IWORK1-1)26,5310,26                                       1806
5310  ALAM(1)=ALAM(1)+WORK1                                        1807
      GO TO 26                                                     1808
532   IF(NREACT(1)-16)534,533,533                                  1809
533   ICOLL(IWORK1)=2                                              1810
      IF(IWORK1-1)26,5330,26                                       1811
5330  ALAM(2)=ALAM(2)+WORK1                                        1812
      GO TO 26                                                     1813
534   DO 535 I=1,NLWREV                                            1814
      IF(NOLAW(1)-LAWREV(I))535,536,535                            1815
535   CONTINUE                                                     1816
      ICOLL(IWORK1)=3                                              1817
      LAWTP(IWORK1)=1                                              1818
      IF(IWORK1-1)26,5350,26                                       1819
5350  ALAM(3)=ALAM(3)+WORK1                                        1820
      GO TO 26                                                     1821
536   ICOLL(IWORK1)=LWNO(I)+3                                      1822
      LAWTP(IWORK1)=LWNO(I)+1                                      1823
      IF(IWORK1-1)26,5360,26                                       1824
5360  ALAM(I+3)=ALAM(I+3)+WORK1                                    1825
26    IF(NSECS)32,507,27                                           1826
27    WORK10=WOUT                                                  1827
      DO 31 I=1,NSECS                                              1828
      WORK12=EOUT(I)                                               1829
      WORK9=UOUT(I)                                                1830
      IF(WORK12-THERM)28,29,29                                     1831
28    WORK12=THERM                                                 1832
      WORK9=LOG (THERM/0.25E-7)                                   NBS1833
29    ANGLE=COSPHI(I)                                              1834
      CALL TWIST(ANGLE)                                            1835
```

```
      CALL WRTBT                                                        1836
      IF(NSENSE)30,31,30                                                1837
30    PRINT                    34,ANEUNO,IWORK1,EOUT(I),UOUT(I),WOUT,WORK13,  1838
     2WORK14,WORK15,WORK16,WORK17,WORK18,WORK19,ISCOLM,NONUC(I),NOACT(I)  1839
     3,NORNGE(I),NOLAW(I),NSECS                                         1840
31    CONTINUE                                                          1841
32    GO TO 1                                                           1842
33    FORMAT(1H0,F7.0,I4,9F7.3,F10.4,I5,3I6,I5,I7)                      1843
34    FORMAT(1X,F7.0,I4,9F7.3,F10.4,I5,3I6,I5,I7)                       1844
      END                                                               1845
```

```
      SUBROUTINE INPUT                                                          0123
C                                                                               0204
C     GENERAL INPUT FOR TRUNCATED CONE, INCIDENT NEUTRONS ALONG THE AXISNBS0205
C                                                                               0206
      INCLUDE CINC1                                                          NBS
      DIMENSION STDIST(25),ANGS(25),AREA(25),NOACA(24)                       NBS0207
      READ(5,201)IFB4,NSENSE                                                 NBS0219
      READ(5,202)HITE,FRAD,ANGLE                                             NBS0224
      WRITE(6,204)HITE,FRAD,ANGLE                                            NBS0225
  204 FORMAT(46H0THE SCATTERER IS A TRUNCATED CONE OF LENGTH =,F7.3,          NBS0226
     127HCMS, ENTRANCE FACE RADIUS =,F7.3,21HCMS, AND HALF ANGLE =,          NBS0226A
     2F7.5,8HRADIANS.)                                                       NBS0226B
      HITE=HITE/2.                                                           NBS0226C
      READ(5,201)JOBFIN,ITMAG                                                0227
      READ(5,202)           SAMPLE                                           0228
      WRITE(6,2040)            JOBFIN,SAMPLE                                 0229
 2040 FORMAT(14H0THERE WILL BE,I3,16H SAMPLES EACH OF,F8.0,10H NEUTRONS.     0230
     2)                                                                      0231
      IF(ITMAG-1)2043,2042,2043                                              0232
 2042 WRITE(6,2041)                                                          0233
 2041 FORMAT(1H ,31H AUTOMATIC ITERATION REQUESTED.,10X,17H ONE SAMPLE O     0234
     1NLY.)                                                                  0235
      JOBFIN=1                                                               0236
 2043 READ(5,202)STRTE                                                       0237
      IF(STRTE)205,206,205                                                   0238
  205 WRITE(6,207)             STRTE                                         0239
  207 FORMAT(21H0STARTING ENERGY IS =,F8.3,4H MEV)                           0240
      GO TO 208                                                              0241
  206 WRITE(6,209)                                                           0242
  209 FORMAT(41H0STARTING ENERGY IS FROM FISSON SPECTRUM.)                    0243
  208 READ(5,202)             DIST                                          0244
      THETAM=COS(ATAN(FRAD/(-DIST-HITE)))                                 NBS0245
      WRITE(6,210)THETAM,DIST                                                0247
  210 FORMAT(71H0COSINE OF SEMI-VERTICAL ANGLE OF THE CONE JUST ENCLOSIN     0248
     2G THE SAMPLE  =,F8.6,12H FROM SOURCE,F6.2,22H CMS ALONG THE X AXISNBS0249
     3.)                                                                     0250
```

```
      READ(5,201)NSTDP                                                  0251
      READ(5,202)(ANGS(I),STDIST(I),I=1,NSTDP)                          0252
      WRITE(6,2010)(ANGS(I),STDIST(I),I=1,NSTDP)                        0253
 2010 FORMAT(31HOSTART DISTRIBUTION PROVIDED IS /9(6F10.4/))            0254
 201  FORMAT(6I10)                                                      0255
 202  FORMAT(6F10.4)                                                    0256
C     DEFINE START DISTRIBUTION TO INCLUDE THE MINIMUM ANGLE WHICH WILL 0257
C     JUST ENCLOSE THE SAMPLE (USUALLY ABOUT 10-16 DEGREES) BY UP TO 25 NBS0258
C     POINTS.                                                           0259
      DO 211 I=1,NSTDP                                                  0260
      ANGS(I)=COS (ANGS(I)/57.295828)                                   NBS0261
 211  CONTINUE                                                          0262
      DO 212 I=1,NSTDP                                                  0263
      IF(THETAM-ANGS(I))212,213,213                                     0264
 212  CONTINUE                                                          0265
      WRITE(6,2120)                                                     0266
 2120 FORMAT(41HINSUFFICIENT START DISTRIBUTION PROVIDED.)              0267
      CALL EEXIT                                                        0268
 213  AREA(1)=0.0                                                       0269
      STDIST(I)=STDIST(I-1)-(STDIST(I-1)-STDIST(I))*(ANGS(I-1)-THETAM)/(  0270
     2ANGS(I-1)-ANGS(I))                                                0271
      ANGS(I)=THETAM                                                    0272
      L=I-1                                                             0273
      LI=I-1                                                            0274
      DO 214 K=1,L                                                      0275
      AREA(K+1)=AREA(K)+((STDIST(K+1)+STDIST(K))/2.0)*(ANGS(K)-ANGS(K+1)  0276
     2)                                                                 0277
 214  CONTINUE                                                          0278
      DO 215 K=1,64                                                     0279
      AI=K                                                              0280
      SEG=(AREA(I)*(2.0*AI-1.0))/128.0                                  0281
      DO 216 L=1,I                                                      0282
      IF(AREA(L)-SEG)216,217,218                                        0283
 216  CONTINUE                                                          0284
      WRITE(6,2160)                                                     0285
 2160 FORMAT(63H1ERROR IN INPUT. PARTIAL SUM LRSS THAN THE TOTAL.  CALL  0286
```

```
     2EXIT.  )                                                                  0287
      CALL EExIT                                                                0288
217   CNPHI(K)=ANGS(L)                                                          0289
      GO TO 215                                                                 0290
218   GRAD=(STDIST(L)-STDIST(L-1))/(ANGS(L)-ANGS(L-1))                          0291
      IF(GRAD)300,301,300                                                       0292
300   CNPHI(K)=ANGS(L-1)-(STDIST(L-1)-SQRT ((STDIST(L-1)*STDIST(L-1))-2.NBS0293
     20*GRAD*(SEG-AREA(L-1))))/GRAD                                             0294
      GO TO 215                                                                 0295
301   CNPHI(K)=ANGS(L)+(AREA(L)-SEG)/STDIST(L)                                  0296
215   CONTINUE                                                                  0297
      WRITE(6,219)(CNPHI(I),I=1,64)                                             0298
219   FORMAT(55H064 EQUI-PROBABLE COSINES OF THE START DISTRIBUTION ARE/        0299
     2(8F14.6))                                                                 0300
      TANGLE=TAN(ANGLE)                                                 NBS0301
      RINC=HITE*TANGLE*2.                                               NBS0301A
      BRAD=FRAD+RINC                                                    NBS0301B
      FLUXFT=(HITE*(FRAD**2+FRAD*RINC+(RINC**2)/3))/(((DIST+HITE)**2)*  NBS0302
     1(1-THETAM))                                                       NBS0303
      M1=IXMAT+2*NMATS                                                     0304
      FNEGS=NEGS-1.0                                                       0305
      N=M1+4*NMATS                                                         0307
      MISSM=IDATA(N)                                                       0308
      UIN=LOG (STRTE/0.25E-7)                                           NBS
      S=STRTE                                                           EU.
      LGR=1                                                             EU.
      IF(S-EMC(1))5000,5000,4999                                        EU.NBS
4999  IF(NEGS-128)4001,4001,5001                                        EU.
5001  M=129                                                             EU.
      LGR=M                                                             EU.NBS
      IF(S-EMC(M))5002,5000,5003                                        EU.
5002  M=M-64                                                            EU.
      GO TO 4020                                                        EU.
5003  M=M+64                                                            EU.
      GO TO 4020                                                        EU.
4001  M=65                                                              EU.
```

```
4020 LGR=M                                                          EU.
     IF(S-EMC(M))4030,5000,4040                                     EU.
4030 M=M-32                                                         EU.
     GO TO 4050                                                     EU.
4040 M=M+32                                                         EU.
4050 LGR=M                                                          EU.
     IF(S-EMC(M))4060,5000,4070                                     EU.
4060 M=M-16                                                         EU.
     GO TO 4080                                                     EU.
4070 M=M+16                                                         EU.
4080 LGR=M                                                          EU.
     IF(S-EMC(M))4090,5000,4100                                     EU.
4090 M=M-8                                                          EU.
     GO TO 4110                                                     EU.
4100 M=M+8                                                          EU.
4110 LGR=M                                                          EU.
     IF(S-EMC(M))4120,5000,4130                                     EU.
4120 M=M-4                                                          EU.
     GO TO 4140                                                     EU.
4130 M=M+4                                                          EU.
4140 LGR=M                                                          EU.
     IF(S-EMC(M))4150,5000,4160                                     EU.
4150 M=M-2                                                          EU.
     GO TO 4170                                                     EU.
4160 M=M+2                                                          EU.
4170 LGR=M                                                          EU.
     IF(S-EMC(M))4180,5000,4190                                     EU.
4180 M=M-1                                                          EU.
     GO TO 4200                                                     EU.
4190 M=M+1                                                          EU.
4200 LGR=M                                                          EU.
     IF(S-EMC(M))4210,5000,5000                                     EU.
4210 LGR=M-1                                                        EU.
5000 M2=IDATA(M1)+LGR-MISSM                                         EU.
     AVPATH=DATA(M2)                                                0313
     FLUXFT=FLUXFT/AVPATH                                           0314
```

```
      AVCOS=(CNPHI(32)+CNPHI(33))/2.0                                          0315
      DO 2150 I=1,LI                                                           0316
      IF(ANGS (I+1)-AVCOS)2151,2152,2150                                       0317
 2150 CONTINUE                                                                 0318
      I=LI                                                                     0319
 2151 FACT=STDIST(I)-(STDIST(I)-STDIST(I+1))*((ANGS (I)-AVCOS)/(ANGS (I)       0320
     2-ANGS (I+1)))                                                            0321
      GO TO 2153                                                               0322
 2152 FACT=STDIST(I)                                                           0323
 2153 FLUXFT=FLUXFT*STDIST(1)/FACT                                             0324
      READ(5,201)NLWREV                                                        0325
      READ(5,220)(LAWREV(I),LWNO(I),I=1,NLWREV)                                0326
      WRITE(6,2193)                                                            0327
 2193 FORMAT(38H0LAW REFERENCE NUMBER  M.C.LAW NUMBER.)                        0328
      WRITE(6,2194)(LAWREV(I),LWNO(I),I=1,NLWREV)                              0329
 2194 FORMAT(I10,10X,I10)                                                      0330
      IF(IFB4)2192,234,2192                                                    0339
 2192 READ(5,201)IANALA,IANALB,IANALC,IANALD                                   0340
      READ(5,201)NANAL                                                         0341
      READ(5,220)            (NUCL(I),NAC1(I),I=1,NANAL)                       0342
 220  FORMAT(2I10)                                                             0343
      WRITE(6,221)NANAL                                                        0344
 221  FORMAT(15H0B4 ANALYSIS ON,I3,10H ACTIONS. )                              NBS0345
      WRITE(6,222)             (NUCL(I),I=1,NANAL)                             0346
 222  FORMAT(15H0NUCLIDE NOS.  ,24I4)                                          0347
      WRITE(6,223)             (NAC1(I),I=1,NANAL)                             0348
 223  FORMAT(16H0K.P.ACTION NOS.,I3,23I4)                                      0349
      M3=M1-NMATS                                                              0350
      IXNUC1=IDATA(M3)                                                         0351
      M4=M3+4*NMATS                                                            0352
      NUCS=IDATA(M4)                                                           0353
      DO 3 I=1,NANAL                                                           0354
      M5=IXNUC1+NUCL(I)                                                        0355
      M6=8*NUCS+M5                                                             0356
      NOACA(I)=IDATA(M6)                                                       0357
      IXACT1(I)=IDATA(M5)                                                      0358
```

```
      MMM=2*NOACA(I)+IXACT1(I)                                                  0359
      K=1                                                                       0360
      NOACA1=NOACA(I)                                                           0361
      DO 4 J=1,NOACA1                                                           0362
      L=MMM+K                                                                   0363
      IF(IDATA(L)-NAC1(I))7,5,7                                                 0364
 7    K=K+1                                                                     0365
 4    CONTINUE                                                                  0366
      WRITE(6,6)              NAC1(I)                                           0367
      CALL EXIT                                                                 0368
 5    NACT(I)=K                                                                 0369
 3    CONTINUE                                                                  0370
 6    FORMAT(18H K.P.ACTION NUMBER,I4,29H DOES NOT APPEAR IN THE DATA.)         0371
      WRITE(6,224)              (NACT(I),I=1,NANAL)                             0372
 224  FORMAT(15H0M.C.ACTION NO.,24I4)                                           0373
      READ(5,202)(FCCOS(I),I=1,33)                                              0374
C     33 COSINES WITH 33 VALUES OF THE ANGULAR DISTRIBUTION MUST BE             0375
C     SUPPLIED, WITH MONOTONICALLY INCREASING VALUES OF THE COSINE.     NBS0376
      DO 225 J=1,NANAL                                                          0377
      READ(5,202)(FCVAL(J,I),I=1,33)                                            0378
      AREB=0.0                                                                  0379
      DO 228 I=1,32                                                             0380
      AREB=AREB+ABS (FCCOS(I+1)-FCCOS(I))*((FCVAL(J,I)+FCVAL(J,I+1))/2.0NBS0381
     2)                                                                         0382
 228  CONTINUE                                                                  0383
      IA=1                                                                      0384
      IB=15                                                                     0385
 2280 WRITE(6,226)(FCCOS(I),I=IA,IB)                                            0386
 226  FORMAT(15H0COSINES        ,15F7.3)                                        0387
      WRITE(6,227)(FCVAL(J,I),I=IA,IB)                                          0388
 227  FORMAT(15H DISTRIBUTION   ,15F7.3)                                        0389
      DO 229 I=IA,IB                                                            0390
      FCVAL(J,I)=FCVAL(J,I)/AREB                                                0391
 229  CONTINUE                                                                  0392
      WRITE(6,230)(FCVAL(J,I),I=IA,IB)                                          0393
 230  FORMAT(15H DIFF. X SECT. ,15F7.3)                                         0394
```

```
      IF(IA-1)2300,2300,2301                                                    0395
2300  IA=16                                                                     0396
      IB=30                                                                     0397
      GO TO 2280                                                                0398
2301  IF(IA-16)2302,2302,225                                                    0399
2302  IA=31                                                                     0400
      IB=33                                                                     0401
      GO TO 2280                                                                0402
225   CONTINUE                                                                  0403
      IMINM=1                                                                   0404
      DO 252 L=1,NANAL                                                          0405
      IMIN(L)=IMINM                                                             0406
      READ(5,250)IMAX(L)                                                        0407
250   FORMAT(I10)                                                               0408
      PRINT 251,IMAX(L),L                                                       0409
251   FORMAT(10HUTHERE ARE,I2,46H SUPPLEMENTARY RANGES ASSOCIATED WITH ANBS0410
     2NALYSIS,I2)                                                             0411
      IF(IMAX(L))252,252,253                                                    0412
253   IMAXM=IMAX(L)-1+IMINM                                                     0413
      DO 254 I=IMINM,IMAXM                                                      0414
      READ(5,202)ENVAL(L,I)                                                     0415
      READ(5,202)(SUPVAL(I,K),K=1,33)                                           0416
      AREB=0.0                                                                  0417
      DO 258 J=1,32                                                             0418
      AREB=AREB+ABS (FCCOS(J+1)-FCCOS(J))*((SUPVAL(I,J)+SUPVAL(I,J+1))/2NBS0419
     2.0)                                                                     0420
258   CONTINUE                                                                  0421
      IA=1                                                                      0422
      IB=15                                                                     0423
259   WRITE(6,2580)ENVAL(L,I)                                                   0424
2580  FORMAT(25HOTHIS RANGE APPLIES BELOW,F7.4,5H MEV.)                         0425
      WRITE(6,226)(FCCOS(J),J=IA,IB)                                            0426
      WRITE(6,227)(SUPVAL(I,J),J=IA,IB)                                         0427
      DO 260 J=IA,IB                                                            0428
      SUPVAL(I,J)=SUPVAL(I,J)/AREB                                              0429
260   CONTINUE                                                                  0430
```

```
      WRITE(6,230)(SUPVAL(I,J),J=IA,IB)                                  0431
      IF(IA-1)261,261,262                                                0432
261   IA=16                                                              0433
      IB=30                                                              0434
      GO TO 259                                                          0435
262   IF(IA-16)263,263,254                                               0436
263   IA=31                                                              0437
      IB=33                                                              0438
      GO TO 259                                                          0439
254   CONTINUE                                                           0440
      IMINM=IMAXM+1                                                     NBS0441
      IF(IMAXM-24)252,252,256                                            0442
256   WRITE(6,257)                                                       0443
257   FORMAT(27H1IMAX HAS EXCEEDED 24-HALT.)                             0444
      CALL EEXIT                                                         0445
252   CONTINUE                                                           0446
      READ(5,201)NOCOU                                                   0447
      READ(5,202)            (COUNT(I),I=1,NOCOU)                        0448
      WRITE(6,232)             NOCOU,(COUNT(I),I=1,NOCOU)                0449
232   FORMAT(10H0THERE ARE,I3,56H COUNTERS LOCATED AROUND THE EQUATOR OFNBS0450
     2 THE SCATTERER AT/(10F9.4))                                       NBS0451
      READ(5,201)           NENSP                                        0452
      READ(5,202)           (ENSP(I),I=1,NENSP)                          0453
      WRITE(6,233)            (ENSP(I),I=1,NENSP)                        0454
233   FORMAT(48H0THE ENERGY SPECTRA OF THE B4 ANALYSIS CELLS ARE/(10F9.3   0455
     2))                                                                 0456
234   DO 2340 K=1,32                                                     0457
      FCCOSD(K)=FCCOS(K+1)-FCCOS(K)                                      0458
2340  CONTINUE                                                           0459
      RETURN                                                             0460
      END                                                                0463
```

```
      SUBROUTINE CRNEU                                                    3036
C
C     TRUNCATED CONE SCATTERING SAMPLE, INCIDENT NEUTRONS ALONG THE AXISNBS
C
      INCLUDE CINC1                                                       NBS
      DIMENSION TEMP(10),TRIG(4)                                          3116
   61 ITEMP=NRANDA(64)                                                    NBS3121
      WORK3=CNPHI(ITEMP)                                                  3122
   62 TEMP(1)=RANDA(-1)                                                   EU.3124
      TEMP(2)=RANDA(-2)                                                   EU.3126
      TEMP(3)=TEMP(1)*TEMP(1)                                             3127
      TEMP(4)=TEMP(2)*TEMP(2)                                             3128
      TEMP(5)=TEMP(3)+TEMP(4)                                             3129
      IF(TEMP(5))62,62,63                                                 3130
 63   IF(TEMP(5)-1.0)64,62,62                                             3131
 64   TRIG(1)=(TEMP(3)-TEMP(4))/TEMP(5)                                   3132
      TRIG(2)=(2.0*TEMP(1)*TEMP(2))/TEMP(5)                               3133
      TRIG(3)=SQRT (1.0-WORK3*WORK3)                                      NBS3134
      WORK4=TRIG(1)*TRIG(3)                                               3135
      WORK5=TRIG(2)*TRIG(3)                                               3136
C                                                                         3137
C     DOES THE NEUTRON HIT THE TARGET                                     3138
C                                                                         3139
      TEMP(1)=FRAD+(DIST+HITE)*TRIG(3)/WORK3                              NBS3140
      IF(TEMP(1))67,67,65                                                 3142
   65 TEMP(2)=-(DIST+HITE)/WORK3                                          NBS3143
   66 WORK6=-HITE                                                         NBS3145
      WORK7=WORK4*TEMP(2)                                                 NBS3146
      WORK8=WORK5*TEMP(2)                                                 NBS3147
      ANEUNO=ANEUNO+1.0                                                   3148
      EIN=STRTE                                                           3149
      UIN=LOG (EIN/0.25E-7)                                               NBS3150
      MAT=1                                                               NBS3151
      IWORK1=0                                                            3152
      WORK19=0.0                                                          3153
      WIN=1.0                                                             3154
```

```
      WORK11=0.0                                                        3155
      IWORK2=0                                                          3156
      RETURN                                                            3157
67    AMISS=AMISS+1.0                                                   3158
      GO TO 61                                                          3159
      END                                                               3160
```

```
      SUBROUTINE TRACK
C     TRACKS NEUTRONS IN A TRUNCATED CONE WITH AXIS LYING ALONG THE NEUTRON BEAM
      INCLUDE CINC1
      CALL EGMV
      PATHL=(-(LOG(RANDA(1))))*PATH
      IF(WORK3)1,6,2
    1 TRS=-(HITE+WORK6)/WORK3
      RAD2=FRAD**2
      GO TO 3
    2 TRS=(HITE-WORK6)/WORK3
      RAD2=BRAD**2
    3 WORK17=WORK7+TRS*WORK4
      WORK18=WORK8+TRS*WORK5
      TRR2=WORK17**2+WORK18**2
      IF(RAD2.LT.TRR2)GO TO 6
      IF(TRS.GT.PATHL)GO TO 13
      ISCOLL=2
      IF(WORK3.GT.0)GO TO 4
      WORK16=-HITE
      GO TO 5
    4 WORK16=HITE
    5 WORK19=WORK19+TRS/SPEED
      RETURN

    6 CALL FONEC(PATHL)
      IF(HITE.LE.ABS(WORK16))GO TO 7
      TRA2=WORK17**2+WORK18**2
      RAD2=(FRAD+(HITE+WORK16)*TANGLE)**2
      IF(RAD2.GT.TRA2)GO TO 14
    7 ISCOLL=1
      NRTS=0
      RAD=FRAD+(HITE+WORK6)*TANGLE
      TA=1.-WORK3**2*(1.+TANGLE**2)
      TB=WORK7*WORK4+WORK8*WORK5-WORK3*TANGLE*RAD
```

```
      TC=WORK7**2+WORK8**2-RAD**2
      IF(ABS(TA).GT.1.E-30)GO TO 8
      IF(ABS(TB).LT.1.E-30)GO TO 21
      TR=-TC/(2.*TB)
      GO TO 12
    8 TD=TB*TB-TA*TC
      IF(TD)15,10,9
    9 TE=-TB+SQRT(TD)
      IF(TE.LT.0)GO TO 10
      NRTS=1
      TR=TE/TA
   10 TE=-TB-SQRT(TD)
      IF(TE.LT.0)GO TO 11
      NRTS=NRTS+1
      TR=TE/TA
   11 IF(NRTS-1)17,12,19
   12 CALL FONEC(TR)
      WORK19=WORK19+TR/SPEED
      RETURN

   13 CALL FONEC(PATHL)
   14 ISCOLL=3
      WORK19=WORK19+PATHL/SPEED
      RETURN

C     ERROR EXITS

   15 WRITE(6,16)
   16 FORMAT(24H IMAGINARY ROOT IN TRACK)
      GO TO 23
   17 WRITE(6,18)
   18 FORMAT(26H NO POSITIVE ROOT IN TRACK)
      GO TO 23
   19 WRITE(6,20)
   20 FORMAT(28H TWO POSITIVE ROOTS IN TRACK)
      GO TO 23
```

```
21 WRITE(6,22)
22 FORMAT(28H INDETERMINATE ROOT IN TRACK)
23 WRITE(6,24)WORK3,WORK4,WORK5,WORK6,WORK7,WORK8,PATHL
24 FORMAT(7F10.3)
   CALL EEXIT
   END
```

```
      SUBROUTINE NAPAN                                                  3371

      INCLUDE CINC1                                                     NBS
      DIMENSION FACT(33),PATHLL(33),ANGLEE(33),KL(33)                   NBS3451
      NENSP1=NENSP-1                                                    3453
      M1=IXMAT+NMATS+MAT                                                3454
      N=M1+4*NMATS                                                      3455
      MISSM=IDATA(N)                                                    3456
      M2=IDATA(M1)-MISSM                                                3457
      DO 1 I=1,NOCOU                                                    3458
      COSOM=COUNT(I)                                                    3459
      CALL FPATH(COSOM,PATHL,ANGLEF)                                    NBS3460
      DO 2 K=1,32                                                       3461
      IF(FCCOS(K+1)-ANGLEF)2,3,3                                        NBS3462
2     CONTINUE                                                          3463
      K=32                                                              3464
3     AFCOS=FCCOS(K)                                                    3465
      FACT(I)=(ANGLEF-AFCOS)/FCCOSD(K)                                  NBS3466
      PATHLL(I)=PATHL                                                   3467
      ANGLEE(I)=ANGLEF                                                  NBS3468
      KL(I)=K                                                           3469
1     CONTINUE                                                          3470
      DO 7 J=1,NANAL                                                    3471
      NFORM=0                                                           3472
      NAC=NAC1(J)                                                       3473
      NUCLID=NUCL(J)                                                    3474
      PART=PART1(J)                                                     3475
      ATOM=ATOM1(J)                                                     3476
      WSQ=ATOM*ATOM-1.0                                                 3477
      DO 6 I=1,NOCOU                                                    3478
      K=KL(I)                                                           3479
      AS=ANGLEE(I)                                                      3480
      FACTOR=FACT(I)                                                    3481
      PATHL=PATHLL(I)                                                   3482
      ASQ=AS*AS                                                         3483
      IF(PART)7,7,8                                                     3484
```

```
8     IF(NAC-2)9,10,9                                                    3485
10    X=SQRT (ASQ+WSQ)                                                  NBS3486
      P=((AS+X)/(ATOM+1.0))*((AS+X)/(ATOM+1.0))                          3487
      REDEN=EIN*P                                                        3488
      GO TO 11                                                           3489
9     IF(NFORM)34,34,35                                                  3490
34    CALL CREN                                                          3491
      REDEN=ENER                                                         3492
      IF(REDEN)38,11,11                                                  3493
35    GO TO (36,11,11,11,11,11,11,11,36,11,11,11,11,11,11,11),NFORM     NBS3494
36    P=(AS+SQRT (ASQ+ATOM*QV*(1.0+ATOM)/EIN+WSQ))/(1.0+ATOM)           NBS3495
      REDEN=EIN*P*P                                                      3496
  11  IF(IMAX(J).LE.0)GO TO 15                                          NBS3503
      IMINM=IMIN(J)                                                     NBS3504
      IMAXM=IMINM+IMAX(J)-1                                             NBS3505
      DO 50 JJ=IMINM,IMAXM                                              NBS3506
      IF(EIN-ENVAL(J,JJ))50,51,52                                       NBS3507
  50  CONTINUE                                                          NBS3508
  51  KK=JJ                                                             NBS3509
      GO TO 19                                                          NBS3510
  52  IF(JJ.LE.IMINM)GO TO 15                                           NBS3511
      KK=JJ-1                                                           NBS3512
      GO TO 19                                                           3513
15    SIGMA=(FCVAL(J,K+1)-FCVAL(J,K))*FACTOR+FCVAL(J,K)                  3514
      GO TO 16                                                           3515
19    SIGMA=(SUPVAL(KK,K+1)-SUPVAL(KK,K))*FACTOR+SUPVAL(KK,K)            3516
16    DO 20 L=1,NENSP1                                                   3517
      IF(ENSP(L+1)-REDEN)20,21,21                                        3518
20    CONTINUE                                                           3519
      L=NENSP1                                                           3520
 21   S=REDEN                                                           EU.
      LGR=1                                                             EU.
      IF(S-EMC(1))5000,5000,4999                                        NBS EU.
4999  IF(NEGS-128)4001,4001,5001                                        EU.
5001  M=129                                                             EU.
      LGR=M                                                             EU.NBS
```

```
      IF(S-EMC(M))5002,5000,5003                                        EU.
5002  M=M-64                                                            EU.
      GO TO 4020                                                        EU.
5003  M=M+64                                                            EU.
      GO TO 4020                                                        EU.
4001  M=65                                                              EU.
4020  LGR=M                                                             EU.
      IF(S-EMC(M))4030,5000,4040                                        EU.
4030  M=M-32                                                            EU.
      GO TO 4050                                                        EU.
4040  M=M+32                                                            EU.
4050  LGR=M                                                             EU.
      IF(S-EMC(M))4060,5000,4070                                        EU.
4060  M=M-16                                                            EU.
      GO TO 4080                                                        EU.
4070  M=M+16                                                            EU.
4080  LGR=M                                                             EU.
      IF(S-EMC(M))4090,5000,4100                                        EU.
4090  M=M-8                                                             EU.
      GO TO 4110                                                        EU.
4100  M=M+8                                                             EU.
4110  LGR=M                                                             EU.
      IF(S-EMC(M))4120,5000,4130                                        EU.
4120  M=M-4                                                             EU.
      GO TO 4140                                                        EU.
4130  M=M+4                                                             EU.
4140  LGR=M                                                             EU.
      IF(S-EMC(M))4150,5000,4160                                        EU.
4150  M=M-2                                                             EU.
      GO TO 4170                                                        EU.
4160  M=M+2                                                             EU.
      IF(S-EMC(M))4180,5000,4190                                        EU.
4170  LGR=M                                                             EU.
4180  M=M-1                                                             EU.
      GO TO 4200                                                        EU.
4190  M=M+1                                                             EU.
```

```
4200 LGR=M                                                              EU.
     IF(S-EMC(M))4210,5000,5000                                         EU.
4210 LGR=M-1                                                            EU.
5000 M3=M2+LGR                                                          EU.
     PATHB=(-DATA(M3))                                                     3524
     QU=Q(J)                                                               3525
     PTH=PATHL/PATHB                                                       3526
     ADD=QU*SIGMA*EXP (PTH)                                                3527
     DEA(I,L)=DEA(I,L)+ADD                                             NBS3529
     IF(NAC.NE.2)GO TO 24                                              NBS3530
     IF(IWORK1.LE.1)GO TO 23                                           NBS3531
     III=IWORK1-1                                                      NBS3532
     DO 22 II=1,III                                                    NBS3533
     IF(ICOLL(II).NE.1)GO TO 24                                        NBS3534
  22 CONTINUE                                                          NBS3535
  23 DEB(I,L)=DEB(I,L)+ADD                                             NBS3537
     IF(IWORK1.LE.1)GO TO 6                                            NBS3539
     DED(I,L)=DED(I,L)+ADD                                             NBS3540
     GO TO 6                                                               3541
  24 DEC(I,L)=DEC(I,L)+ADD                                             NBS3543
6    CONTINUE                                                              3544
7    CONTINUE                                                              3545
     GO TO 40                                                              3546
38   PRINT 39,REDEN                                                        3547
39   FORMAT(1H0,F10.4,32HNEGATIVE ENERGY COMPUTED IN CREN)                 3548
     CALL EXIT                                                             3549
40   RETURN                                                                3550
     END                                                                   3551
```

```
      SUBROUTINE FPATH(COSOM,PATHL,ANGLEF)

C     PATHLENGTH AND ANGLE FOR B4 ANALYSIS, FOR TRUNCATED CONE SAMPLE.
C     AXIS ALONG THE INCIDENT NEUTRON BEAM.

      INCLUDE CINC1

C     NEUTRON OUT AT 90 DEGREES.
      IF(ABS(COSOM).GE.1.E-5)GO TO 1
      ANGLEF=WORK4
      TSQ=TANGLE**2
      XPR=FRAD/TANGLE+HITE+WORK16
      PATHL=SQRT(XPR*XPR*TSQ-WORK18**2)-WORK17
      RETURN

C     NEUTRON OUT ENTRANCE FACE
    1 SINOM=SQRT(1.-COSOM**2)
      ANGLEF=COSOM*WORK3+SINOM*WORK4
      IF(COSOM.GT.0)GO TO 2
      IF(FRAD.LT.ABS(WORK18))GO TO 3
      FTAN=(SQRT(FRAD**2-WORK18**2)-WORK17)/(HITE+WORK16)
      TANOM=SINOM/COSOM
      IF(FTAN+TANOM.LT.0)GO TO 3
      PATHL=-(HITE+WORK16)/COSOM
      RETURN

C     NEUTRON OUT EXIT FACE
    2 BTAN=(SQRT(BRAD**2-WORK18**2)-WORK17)/(HITE-WORK16)
      TANOM=SINOM/COSOM
      IF(BTAN.LT.TANOM)GO TO 3
      PATHL=(HITE+WORK16)/COSOM
      RETURN

C     NEUTRON OUT THE SIDE, BUT NOT AT 90 DEGREES, NORMAL SOLUTION.
    3 TSQ=TANGLE**2
      XPR=FRAD/TANGLE+HITE+WORK16
```

```
      PA=SINOM**2-(COSOM**2)*TSQ
      PB=WORK17*SINOM-XPR*COSOM*TSQ
      PC=WORK17**2-(XPR**2)*TSQ+WORK18**2
      IF(ABS(PA).LT.1.E-30)GO TO 4
      PATHL=(SQRT(PB**2-PA*PC)-PB)/PA
      RETURN

C     LINEAR SOLUTION
    4 PATHL=-PC/(2.*PB)
      RETURN
      END
```

```
      SUBROUTINE FPATH(COSOM,PATHL,ANGLEF)
C
C     PATHLENGTH AND ANGLE FOR THE B4 ANALYSIS, FOR A CYLINDRICAL SAMPLE
C     WITH ITS AXIS ALONG THE INCIDENT NEUTRON BEAM.
C
      INCLUDE CINC1
      PATHL=SQRT(FRAD**2-WORK18**2)-WORK17
      IF(ABS(COSOM).GT.1E-5)GO TO 1
      ANGLEF=WORK4
      GO TO 3
    1 SINOM=SQRT(1-COSOM**2)
      TANOM=SINOM/COSOM
      ANGLEF=COSOM*WORK3+SINOM*WORK4
      IF(COSOM.GT.1E-5)GO TO 2
      FTAN=PATHL/(HITE+WORK16)
      IF((FTAN+TANOM).LT.1E-5)GO TO 3
      PATHL=-(HITE+WORK16)/COSOM
      RETURN
    2 FTAN=PATHL/(HITE-WORK16)
      IF(FTAN.LT.TANOM)GO TO 3
      PATHL=(HITE+WORK16)/COSOM
      RETURN
    3 PATHL=PATHL/SINOM
      RETURN
      END
```

```
      SUBROUTINE OUTPUT                                                  3878
C     OUTPUTS RESULTS AT THE END OF EACH SAMPLE.                         3879

      INCLUDE CINC1                                                      NBS
      DIMENSION P(33)                                                    3958
      PRINT              1,(HEAD(I),I=1,12)                              3960
 1    FORMAT(12A6)                                                       3961
      PRINT              2,NOSAMP                                        3962
 2    FORMAT(1H0,52X,13HSAMPLE NUMBER,I3)                                3963
      PRINT              3,SAMPLE                                        3964
 3    FORMAT(1H0,40X,F8.0,33H NEUTRONS STARTED IN EACH SAMPLE.)          3965
      PART =NOSAMP                                                       3966
      TOT=PART*SAMPLE                                                    3967
      PRINT              5,TOT                                           3968
 5    FORMAT(1H0,39X,F9.0,35H NEUTRONS HAVE BEEN TRACKED SO FAR.)        3969
      PRINT              4,PESC,CESC                                     3970
 4    FORMAT(24H0PLANE SURFACE ESCAPES =,F11.3/24H0CURVED SURFACE ESCAPE  3971
     2S=,F11.3)                                                         3972
      CALL OUTB3                                                         3973
      I1=NENSP-1                                                         3974
      IF(IFB4.EQ.0)GO TO 7                                              NBS3975
      CALL OUTB4(DEA,1,IANALA)                                          NBS3937
      IF(IANALA.LE.0)GO TO 8                                            NBS3978
      DO 6 I=1,I1                                                       NBS3979
 6    P(I)=DEA(IANALA,I)                                                NBS3980
      CALL APLOT3(P,I1,ENSP,IANALA)                                      3982
 8    CALL OUTB4(DEB,2,IANALB)                                          NBS3984
      IF(IANALB.LE.0)GO TO 10                                           NBS3985
      DO 9 I=1,I1                                                       NBS3986
 9    P(I)=DEB(IANALB,I)                                                NBS3987
      CALL APLOT3 (P,I1,ENSP,IANALB)                                     3989
 10   CALL OUTB4(DEC,3,IANALC)                                          NBS3991
      IF(IANALC.LE.0)GO TO 12                                           NBS3992
      DO 11 I=1,I1                                                      NBS3993
 11   P(I)=DEC(IANALC,I)                                                NBS3994
      CALL APLOT3 (P,I1,ENSP,IANALC)                                     3996
```

```
12    CALL OUTB4(DED,4,IANALD)                                  NBS3998
      IF(IANALD.LE.0)GO TO 7                                    NBS3999
      DO 13 I=1,I1                                              NBS4000
13    P(I)=DED(IANALD,I)                                        NBS4001
      CALL APLOT3 (P,I1,ENSP,IANALD)                               4003
7     RETURN                                                       4004
      END                                                          4005
```

```
      SUBROUTINE AUTO                                                    1977

C  TO ALLOW AUTOMATIC ITERATION UNDER THE FOLLOWING CONDITIONS.          1978
C          NUMBER OF COUNTERS AND INPUT POINTS = 33.                    1979
C          ONE NUCLIDE  ONLY.                                           1980
C          ELASTIC CORRECTION ONLY.                                     1981
C     PHYSICAL ITERATION.
C     (DELTA SIGMA)/(SIGMA) IS THE CHANGE IN THE CROSS SECTION EXCLUDING
C     MULTIPLE SCATTERING.

      INCLUDE CINC1                                                      NBS
      DIMENSION TOTEL(33),CHI(33),ELM2(33),XIP3(33)                      NBS2062
      SUMEL=(DEB(1,33)+DEB(33,33))/32.0                                  2065
      DO 4 J=2,32                                                        2066
      SUMEL=SUMEL+DEB(J,33)/16.0                                         2067
    4 CONTINUE                                                           2068
      IF(ITER.NE.1)GO TO 300                                             NBS2073
      READ(5,101)NTERM,IFCONT                                            NBS2077
  101 FORMAT(2I10)                                                       NBS2078
      NTERM1=NTERM-1                                                     2079
      IF(IFCONT.EQ.0)GO TO 100                                           NBS
      READ(5,104)(EZP(I),I=1,33)                                         NBS
  104 FORMAT(6F10.4)                                                     NBS
      SUMEZP=(EZP(1)+EZP(33))/32                                         NBS
      DO 107 J=2,32                                                      NBS
  107 SUMEZP=SUMEZP+EZP(J)/16                                            NBS
      DO 108 J=1,33                                                      NBS
  108 EZP(J)=EZP(J)/SUMEZP                                               NBS
      GO TO 102                                                          NBS
  100 DO 105 I=1,33                                                      2074
      EZP(1)=FCVAL(1,I)                                                  NBS2075
  105 CONTINUE                                                           2076
  102 IF(NTERM.LE.1)GO TO 300                                            NBS2080
  106 READ(5,103)(SAMP(I),I=1,NTERM)                                     NBS2081
  103 FORMAT(6F10.2)                                                     2082
  300 CHISQ=0.0                                                          2086
```

```
      DO 303 J=1,33                                                    NBS2087
      TOTEL(J)=DED(J,33)/SUMEL                                            2088
      CHI(J)=((TOTEL(J)-EZP(J))**2)/EZP(J)                             NBS2089
      CHISQ=CHISQ+CHI(J)                                                  2090
      DEDNJ=DED(J,33)/SUMEL                                            NBS
      ELM2(J)=FCVAL(1,J)                                                  2097
      FACTOR=(TOTEL(J)-DEDNJ)/ELM2(J)                                  NBS
      IF(ITER.GT.2)GO TO 302                                           NBS
      XIP3(J)=(EZP(J)-DEDNJ)/FACTOR                                    NBS
      GO TO 303                                                        NBS
  302 XIP3(J)=FCVAL(1,J)/FACTOR                                        NBS
  303 CONTINUE                                                            2098
  214 SUM=(XIP3(1)+XIP3(33))/32.0                                         2099
      DO 207 J=2,32                                                       2100
      SUM=SUM+XIP3(J)/16.0                                                2101
  207 CONTINUE                                                            2102
      DO 208 I=1,33                                                       2103
      FCVAL(1,I)=(XIP3(I))/SUM                                            2104
  208 CONTINUE                                                            2105
      DO 220 I=1,33                                                    NBS
  220 XIP3(I)=DEB(I,33)-DED(I,33)                                      NBS
      SUMSEL=(XIP3(1)+XIP(33))/32                                      NBS
      DO 221 I=2,32                                                    NBS
  221 SUMSEL=SUMSEL+XIP3(I)/16                                         NBS
      DO 222 I=1,33                                                    NBS
  222 XIP3(I)=(XIP3(I)/SUMSEL-ELM2(I))/ELM2(I)                         NBS
      PRINT 209,ITER                                                      2106
  209 FORMAT(1H1,20H AFTER ITERATION NO.,I3,49H . NORMALISATION IS UNIT    2107
     1AREA FOR ELASTIC EVENTS.)                                           2108
  216 ITER1=ITER+1                                                        2109
      PRINT 210,ITER,ITER,ITER,ITER1                                      2110
  210 FORMAT(1H0,7HCOUNTER,4X,6HCOSINE,11X,3HEXP,7X,10HOUTPUT NO.,I2,4X,  2111
     13HNO.,I2,5H CHI ,7X,3HNO.,I2,11X,3HNO.,I2,4X,11HDELTA SIGMA,2X,  NBS2112
     27HCOUNTER/2X,6HNUMBER,5X,5HANGLE,10X,5HINPUT,7X,11HALL ELASTIC,6X,  2113
     37HSQUARED,8X,5HINPUT,11X,5HINPUT,9X,6H/SIGMA,2X,6HNUMBER)        NBS2114
      PRINT 111,(J,COUNT(J),EZP(J),TOTEL(J),CHI(J),ELM2(J),FCVAL(1,J),  NBS2115
```

```
   1XIP3(J),J,J=1,33)                                                    NBS2116
111 FORMAT(14,7F15.6,I4)                                                    2117
    PRINT 112,CHISQ                                                         2118
112 FORMAT(1H0,8HCHISQ = ,F10.6)                                            2119
997 IF(ITER-NTERM)415,416,416                                               2120
415 SAMPLE=SAMP(ITER)                                                       2121
    ITER=ITER+1                                                             2122
    GO TO 999                                                               2123
416 ITER=10                                                                 2124
    GO TO 998                                                               2125
999 CALL DATIN                                                              2126
998 RETURN                                                                  2129
    END                                                                     2130
```

```
      SUBROUTINE RANDOM(ISTART)                                          NBS

      DATA MASK/037777777777/,MULTA/30517578125/,C/.29103830E-10/        NBS
      IR=ISTART                                                          NBS
      RETURN                                                             NBS
      ENTRY RDM(R)                                                       NBS
      IR=AND(MASK,IR*MULTA)                                              NBS
      R=C*(FLOAT(IR))                                                    NBS
      RETURN                                                             NBS
      END                                                                NBS


      FUNCTION RANDA(I)                                                  EU.4009

      CALL RDM(R)                                                        NBS4010
      RANDA=R                                                            NBS4010A
      IF(I)1,1,3                                                         EU.4011
    1 RANDA=RANDA*2.-1.                                                  EU.4012
    3 RETURN                                                             EU.4013
      END                                                                EU.4014


      FUNCTION NRANDA(I)                                                 EU.0002

      CALL RDM(XRAND)                                                    NBS0003
      IF(XRAND)10,10,1                                                   EU.0004
    1 IF(XRAND-1.)20,30,30                                               EU.0005
   10 NRANDA=1                                                           EU.0006
      GO TO 40                                                           EU.0007
   20 NRANDA=XRAND*I+1                                                   EU.0008
      GO TO 40                                                           EU.0009
   30 NRANDA=1                                                           EU.0010
   40 RETURN                                                             EU.0011
      END                                                                EU.0012
```

APPENDIX B

A Brief Description of the Components of MAGGIE

1. MAGGIE (Main Program). This program calls the various subroutines required for the analysis, retrieves neutrons from disc storage when required, outputs track parameters if desired, and records the various fates of tracked neutrons.

2. RANDOM (and RDM). This subroutine contains the random number generator, RDM, as a separate entry. RANDOM is called at the beginning of program MAGGIE to enter the starting value for RDM.

3. DATIN serves to set all of the output arrays to zero, and calls ABSYND.

4. ABSYND reads the required nuclear data from the MOULD tape and puts it in encoded sequential storage in the array DATA-IDATA for use during the Monte Carlo tracking.

5. INPUT reads and processes samples and experimental angular distribution data from card input and calculates most of the flux attenuation factor.

6. CRNEU creates random incident neutrons at the entrance face of the sample, in accordance with the input source distribution.

7. TRACK tracks neutrons in the sample, specifying coordinates of collision or escape.

8. EGMV. This subroutine computes the mean free path, velocity, and lethargy group number.

9. FONEC calculates coordinates at the end of a track from initial position, direction cosines, and track length.

10. CR. This subroutine, using random sampling of the information stored by ABSYND from the MOULD data tape, determines all of the parameters of a collision.

11. CALC determines some constants used in subroutine NAPAN.

12. NAPAN. This subroutine calculates and scores the probability of detection at each detector for each collision in the sample.

13. FPATH calculates the path length in the direction of each detector for each collision.

14. CREN is an abbreviated version of CR used by NAPAN that determines only the neutron energy.

15. TWIST chooses new direction cosines after a collision.

16. WRIBT stores any secondary neutrons produced, for recall at the end of the current tracking.

17. OUTPUT, OUTB3, OUTB4 and APLOT3. These subroutines print the results of the calculation.

18. AUTO performs the calculations required for iterative correction of the elastic angular distribution, prints the current output, and calls DATIN to begin the next iteration.

19. END, and its entries EXIT and EEXIT designate normal vs. error exit conditions.

20. TAPLAB returns the tape logical unit label.

21. SRFORT is a subroutine for skipping tape records.

APPENDIX C

Input requirements for MAGGIE-NBS

	FORMAT	VARIABLE	COMMENTS
1.	O12	OCT	Octal starting value for RDM.
2.	12A6	HEAD(I)	Arbitrary heading. Column one should be a 1.
3.	I10	NMATS	The number of materials in the sample. This is always = 1.
4.	I10, E10.4	IDATA(MAT5)	Number of different nuclides in the material.
		DATA(MAT4)	Density of the material.
5.	I10, E10.4	IDATA(K2)	Nuclide reference number (i.e. position on the MOULD tape: see output of MOULD for this).
		DATA(K4)	Proportion of this nuclide in the material. This card is repeated for each nuclide in the material.
6.	2I10	IFB4	Positive for B4 output.
		NSENSE	Positive for track print.
7.	3F10.4	HITE	Length of the samples, in cm.
		FRAD	Entrance radius of same, in cm.
		ANGLE	Half-angle of same, in radians.
8.	2I10	JOBFIN	Number of independant samples (= 1 if ITMAG > 0).
		ITMAG	Positive for automatic iteration.
9.	F10.4	SAMPLE	Number of neutrons in each sample.
10.	F10.4	STRTE	Starting energy in MeV. If the starting energy is set = 0 a fission spectrum is assumed.
11.	F10.4	DIST	Distance from the center of the sample to the source (negative), in cm.
12.	I10	NSTDP	No. of start distribution points to be read in (≤25).
13.	6F10.4	ANGS(I)	Three pairs to a card, the angle and start distribution for that angle. The start distribution need not be normalized, and this card is repeated until NSTDP pairs are read in.

14.	I10	NLWREV	The number of Law Reference numbers for inelastic scatter, i.e. the number of Law Reference numbers to different angular distributions on the MOULD output (P.C.N.'s* 4-15 only) (NLWREV ≤ 50).
15.	2I10	LAWREV(I) LWNO(I)	One pair per card, the above Law Reference numbers and the monotonically increasing "Monte Carlo" law numbers allocated. Any inelastic law not given here will be printed in the B3 section results under Law zero.

NOTE: The following cards are not required if IFB4 ≤ 0.

16.	4I10	IANALA IANALB IANALC IANALD	Four markers, for the tables: A) Complete multiple scatter analysis. B) Elastic events only. C) Inelastic events only. D) Multiple elastic events only. A negative marker suppresses the table. A positive marker = N produces, in addition to the table, a graph for the Nth counter.
17.	I10	NANAL	Number of actions (index I below) (i.e. different neutron processes, such as elastic, inelastic from the 1st excited state, etc.) to be processed by the sub-routine NAPAN.
18.	6F10.4	NUCL(I) NAC1(I)	The nuclide reference number (as in card 5), and the P.C.N.* for each action. There are NANAL such pairs.
19.	6F10.4	FCCOS(J)	Thirty-three values of cosine, including -1 and +1, monotonically increasing.
20.	6F10.4	FCVAL(I,J)	Thirty-three values of the angular distribution (index J) corresponding to the above values of cosines. Repeat for each action (index I) in the same order as in 18.

NOTE: The following three items are repeated, as a group, for each action.

21.	I10	IMAX(I)	Number (index L) of supplementary ranges for this action (even if zero).

*The "P.C.N.'s (Particular Classification Numbers) are listed starting on p.8 of AWRE report no. O 70/63, "The Aldermaston Nuclear Data Library as at May, 1963", K. Parker.

NOTE: The following two items are repeated for each supplementary range. If, for any action, there is no supplementary range these items are omitted.

22.	F10.4	ENVAL(I, L)	Upper limit of the range in MeV. These must be listed in order of decreasing value.
23.	6F10.4	SUPVAL(L, J)	Thirty-three values (index J) of the distribution (range L) at the cosine values FCCOS(J).
24.	I10	NOCOU	Number of counters (≤33).
25.	6F10.4	COUNT(I)	Cosines of counter locations.
26.	I10	NENSP	Number of output energy points (≤33). The output will be classified into the bins formed by these points.
27.	6F10.6	ENSP(I)	Values of output energy points in MeV.
28.	2I10	NTERM IFCONT	Number of iterations (≤10). If this is a continuation of a previous run, for further iterations this should be non-zero (see Section II.c.6.f).
29.	6F10.4	SAMP(I)	Number of neutrons for each iteration, except the first.

NBS TECHNICAL PUBLICATIONS

PERIODICALS

JOURNAL OF RESEARCH reports National Bureau of Standards research and development in physics, mathematics, chemistry, and engineering. Comprehensive scientific papers give complete details of the work, including laboratory data, experimental procedures, and theoretical and mathematical analyses. Illustrated with photographs, drawings, and charts.

Published in three sections, available separately:

• Physics and Chemistry

Papers of interest primarily to scientists working in these fields. This section covers a broad range of physical and chemical research, with major emphasis on standards of physical measurement, fundamental constants, and properties of matter. Issued six times a year. Annual subscription: Domestic, $9.50; foreign, $11.75*.

• Mathematical Sciences

Studies and compilations designed mainly for the mathematician and theoretical physicist. Topics in mathematical statistics, theory of experiment design, numerical analysis, theoretical physics and chemistry, logical design and programming of computers and computer systems. Short numerical tables. Issued quarterly. Annual subscription: Domestic, $5.00; foreign, $6.25*.

• Engineering and Instrumentation

Reporting results of interest chiefly to the engineer and the applied scientist. This section includes many of the new developments in instrumentation resulting from the Bureau's work in physical measurement, data processing, and development of test methods. It will also cover some of the work in acoustics, applied mechanics, building research, and cryogenic engineering. Issued quarterly. Annual subscription: Domestic, $5.00; foreign, $6.25*.

TECHNICAL NEWS BULLETIN

The best single source of information concerning the Bureau's research, developmental, cooperative and publication activities, this monthly publication is designed for the industry-oriented individual whose daily work involves intimate contact with science and technology—*for engineers, chemists, physicists, research managers, product-development managers, and company executives.* Annual subscription: Domestic, $3.00; foreign, $4.00*.

* Difference in price is due to extra cost of foreign mailing.

NONPERIODICALS

Applied Mathematics Series. Mathematical tables, manuals, and studies.

Building Science Series. Research results, test methods, and performance criteria of building materials, components, systems, and structures.

Handbooks. Recommended codes of engineering and industrial practice (including safety codes) developed in cooperation with interested industries, professional organizations, and regulatory bodies.

Special Publications. Proceedings of NBS conferences, bibliographies, annual reports, wall charts, pamphlets, etc.

Monographs. Major contributions to the technical literature on various subjects related to the Bureau's scientific and technical activities.

National Standard Reference Data Series. NSRDS provides quantitive data on the physical and chemical properties of materials, compiled from the world's literature and critically evaluated.

Product Standards. Provide requirements for sizes, types, quality and methods for testing various industrial products. These standards are developed cooperatively with interested Government and industry groups and provide the basis for common understanding of product characteristics for both buyers and sellers. Their use is voluntary.

Technical Notes. This series consists of communications and reports (covering both other agency and NBS-sponsored work) of limited or transitory interest.

Federal Information Processing Standards Publications. This series is the official publication within the Federal Government for information on standards adopted and promulgated under the Public Law 89–306, and Bureau of the Budget Circular A–86 entitled, Standardization of Data Elements and Codes in Data Systems.

CLEARINGHOUSE

The Clearinghouse for Federal Scientific and Technical Information, operated by NBS, supplies unclassified information related to Government-generated science and technology in defense, space, atomic energy, and other national programs. For further information on Clearinghouse services, write:

Clearinghouse
U.S. Department of Commerce
Springfield, Virginia 22151

Order NBS publications from:

Superintendent of Documents
Government Printing Office
Washington, D.C. 20402

U.S. DEPARTMENT OF COMMERCE
WASHINGTON, D.C. 20230

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
U.S. DEPARTMENT OF COMMERCE